Date Logged:	12-SEP
Run Number:	ONE
Depth Driller:	8700
Depth Logger:	8700

Depth Control

Depths Measured From: KELLY BUSHING

Permanent Datum: GROUND LEVEL

Elevation: 1500 K.B. 1485 D.F. 1484 G.L.

Please Write Remarks Like This:

1) Time of Arrival
2) Time Mud Pumps Stopped
3) Time Logger on Bottom
4) Max. Recorded Temperature

Equipment Number: 8317 TLC 04
8317 TLC 05
8317 TLC 06
8317 TLC 07

Type	Weight	Grade	Depth
CSG	13.375	K55	1500
CSG	9.625	N80	8700

CASING AND TUBING DATA

No.	Item Des.	Depth
	TOOL STRING (TOP TO BOTTOM)	
	GR/CCL/TEMP/PRESS/CABLE HEAD	
	MPD_SLIM_3.625_HNGR_2.375_CT_MAND_C	
	MPD_SLIM_3.625_HNGR_2.375_CT_MAND_M	
	MPD_SLIM_3.625_HNGR_2.375_CT_MAND_B	
	BAR WEIGHT	
	MPD_SLIM_3.625_HNGR_2.375_CT_MAND_S	

Depth Scale: 1:240(MEASURED) and

DEPTH	(CCL)	(GR)	(TEMP)	(PRESS)	COMMENTS
8700	0.00	0.00	0.00	0.00	
8675	0.00	0.00	0.00	0.00	
8650	0.00	0.00	0.00	0.00	
8625	0.00	0.00	0.00	0.00	
8600	0.00	0.00	0.00	0.00	
8575	0.00	0.00	0.00	0.00	
8550	0.00	0.00	0.00	0.00	
8525	0.00	0.00	0.00	0.00	
8500	0.00	0.00	0.00	0.00	
8475	0.00	0.00	0.00	0.00	
8450	0.00	0.00	0.00	0.00	
8425	0.00	0.00	0.00	0.00	
8400	0.00	0.00	0.00	0.00	
8375	0.00	0.00	0.00	0.00	
8350	0.00	0.00	0.00	0.00	
8325	0.00	0.00	0.00	0.00	
8300	0.00	0.00	0.00	0.00	
8275	0.00	0.00	0.00	0.00	
8250	0.00	0.00	0.00	0.00	
8225	0.00	0.00	0.00	0.00	
8200	0.00	0.00	0.00	0.00	
8175	0.00	0.00	0.00	0.00	
8150	0.00	0.00	0.00	0.00	
8125	0.00	0.00	0.00	0.00	
8100	0.00	0.00	0.00	0.00	
8075	0.00	0.00	0.00	0.00	
8050	0.00	0.00	0.00	0.00	
8025	0.00	0.00	0.00	0.00	
8000	0.00	0.00	0.00	0.00	
7975	0.00	0.00	0.00	0.00	
7950	0.00	0.00	0.00	0.00	
7925	0.00	0.00	0.00	0.00	
7900	0.00	0.00	0.00	0.00	
7875	0.00	0.00	0.00	0.00	
7850	0.00	0.00	0.00	0.00	
7825	0.00	0.00	0.00	0.00	
7800	0.00	0.00	0.00	0.00	
7775	0.00	0.00	0.00	0.00	
7750	0.00	0.00	0.00	0.00	
7725	0.00	0.00	0.00	0.00	
7700	0.00	0.00	0.00	0.00	
7675	0.00	0.00	0.00	0.00	
7650	0.00	0.00	0.00	0.00	
7625	0.00	0.00	0.00	0.00	
7600	0.00	0.00	0.00	0.00	
7575	0.00	0.00	0.00	0.00	
7550	0.00	0.00	0.00	0.00	
7525	0.00	0.00	0.00	0.00	
7500	0.00	0.00	0.00	0.00	
7475	0.00	0.00	0.00	0.00	
7450	0.00	0.00	0.00	0.00	
7425	0.00	0.00	0.00	0.00	
7400	0.00	0.00	0.00	0.00	
7375	0.00	0.00	0.00	0.00	
7350	0.00	0.00	0.00	0.00	
7325	0.00	0.00	0.00	0.00	
7300	0.00	0.00	0.00	0.00	
7275	0.00	0.00	0.00	0.00	
7250	0.00	0.00	0.00	0.00	
7225	0.00	0.00	0.00	0.00	
7200	0.00	0.00	0.00	0.00	
7175	0.00	0.00	0.00	0.00	
7150	0.00	0.00	0.00	0.00	
7125	0.00	0.00	0.00	0.00	
7100	0.00	0.00	0.00	0.00	
7075	0.00	0.00	0.00	0.00	
7050	0.00	0.00	0.00	0.00	
7025	0.00	0.00	0.00	0.00	
7000	0.00	0.00	0.00	0.00	
6975	0.00	0.00	0.00	0.00	
6950	0.00	0.00	0.00	0.00	
6925	0.00	0.00	0.00	0.00	
6900	0.00	0.00	0.00	0.00	
6875	0.00	0.00	0.00	0.00	
6850	0.00	0.00	0.00	0.00	
6825	0.00	0.00	0.00	0.00	
6800	0.00	0.00	0.00	0.00	
6775	0.00	0.00	0.00	0.00	
6750	0.00	0.00	0.00	0.00	
6725	0.00	0.00	0.00	0.00	
6700	0.00	0.00	0.00	0.00	
6675	0.00	0.00	0.00	0.00	
6650	0.00	0.00	0.00	0.00	
6625	0.00	0.00	0.00	0.00	
6600	0.00	0.00	0.00	0.00	
6575	0.00	0.00	0.00	0.00	
6550	0.00	0.00	0.00	0.00	
6525	0.00	0.00	0.00	0.00	
6500	0.00	0.00	0.00	0.00	

BHA STARTED OUT OF BASKETS, RUNNING SLOWS AND STRAWS.

STARTED TIE-IN RUN 1
STARTED TIE-IN RUN 2
STARTED TIE-IN RUN 3
STARTED TIE-IN RUN 4

TOOLS STARTING BACKING UP HOLE.


CCL
TEMPERATURE (DEG F)
PRESSURE (PSIG)
DEPTH (FEET)
PRESSURE GAUGE @ 8700' (PSIG)
DIFFERENTIAL TEMPERATURE (DEG F)
CCL
GR
TEMP
PRESS
DEPTH
8700
8675
8650
8625
8600
8575
8550
8525
8500
8475
8450
8425
8400
8375
8350
8325
8300
8275
8250
8225
8200
8175
8150
8125
8100
8075
8050
8025
8000
7975
7950
7925
7900
7875
7850
7825
7800
7775
7750
7725
7700
7675
7650
7625
7600
7575
7550
7525
7500
7475
7450
7425
7400
7375
7350
7325
7300
7275
7250
7225
7200
7175
7150
7125
7100
7075
7050
7025
7000
6975
6950
6925
6900
6875
6850
6825
6800
6775
6750
6725
6700
6675
6650
6625
6600
6575
6550
6525
6500
STARTED BACKING UP HOLE @ 8700' FEET
MAXIMUM GAUGE @ 8700' (PSIG)
Tool Tie-In
Tool Tie-In
Tool Tie-In