Schlumberger

Company: Southern California Gas Company

Well: Porter 69B

Field: Aliso Canyon

County: Los Angeles State: California

County: Los Angeles
Field: Aliso Canyon
Location: 848.88' S AND 3183.88' W FROM
Well: Porter 69B
Company: Southern California Gas Company

Ultrasonic Imager

Gamma Ray - CCL

9-5/8" 47# casing

Location:			
848.88' S AND 3183.88' W FROM STATION 84	Elev.:	K.B. 2389.50 ft G.L. 2366.00 ft D.F.	
Permanent Datum: Ground Level	Elev.:	2366.00 f	
Log Measured From: Kelly Bushing	23.50 ft	above Perm.Datum	
Drilling Measured From: Kelly Bushing			

API Serial No.	Section:	Township:	Range:
04-037-24127-00	28	3N	16W

Logging Date		05-Apr-2016	
Run Number		One	
Depth Driller		7258.00 ft	
Schlumberger Depth		7256.00 ft	
Bottom Log Interval		7256.00 ft	
Top Log Interval		60.00 ft	
Casing Fluid Type		Polymer	
Salinity			
Density		9 lbm/gal	
Fluid Level		8.00 ft	
BIT/CASING/TUBING STRING			
Bit Size		12.25 in	
From		1046.00 ft	
To		7344.00 ft	
Casing/Tubing Size		9.625 in	
Weight		47 lbm/ft	
Grade		N80	
From		0.00 ft	
To		7344.00 ft	
Max Recorded Temperatures			
Logger on Bottom	Time	05-Apr-2016 10:50:00	
Unit Number	Location:	3189 Ventura	
Recorded By		I. Kartawidjaja	
Witnessed By		Mr. Tom McMahon	

Disclaimer

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

Contents

1. Header
2. Disclaimer
3. Contents
4. Well Sketch
5. Borehole Size/Casing/Tubing Record
6. Remarks and Equipment Summary
7. Job Event Summary
8. USI Fluid Properties Measurement
9. Composite 1 Main Pass 5 in = 100 ft
   9.1 Integration Summary
   9.2 Software Version
   9.3 Composite Summary
   9.4 Log (LBV1_USI-VDL (DSLT) Cement 9.625inch)
   9.5 Parameter Listing
10. Composite 1 Main Pass 5 IN = 100 FT
   10.1 Integration Summary
   10.2 Composite Summary
   14.2 Composite Summary
   14.3 Log (LBV1_USI Composite 9.625inch)
15. R1D1 Very Hi-res Repeat Corrosion 10 in = 100 ft
   15.1 Integration Summary
   15.2 Composite Summary
   15.3 Log (LBV1_USI Corrosion 9.625inch)
16. R1D1 Very Hi-res Repeat Corrosion 10 in = 100 ft
   16.1 Integration Summary
   16.2 Composite Summary
   16.3 Log (LBV1_USI Corrosion 9.625inch)
17. R1D1 Very Hi-res Repeat Corrosion 10 in = 100 ft
   17.1 Integration Summary
   17.2 Composite Summary
   17.3 Log (LBV1_USI Corrosion 9.625inch)
18. R1D1 Very Hi-res Repeat Corrosion 10 in = 100 ft
   18.1 Integration Summary
   18.2 Composite Summary

10.3 Log (LBV1_USI Composite 9.625inch)
11. Composite 1 Cement Log 2 IN = 100 FT
11.1 Integration Summary
11.2 Composite Summary
11.3 Log (LBV1_USI Cement 9.625inch)
12. Composite 1 Corrosion 5 in = 100 ft
12.1 Integration Summary
12.2 Composite Summary
12.3 Log (LBV1_USI Corrosion 9.625inch)
13. Composite 1 USI Compressed Goodwin
13.1 Integration Summary
13.2 Composite Summary
13.3 Log (Import of USI Goodwin)
14. R1D1 Repeat Pass 5 IN = 100 FT
14.1 Integration Summary
18.3 Log (LBV1_USI Corrosion 9.625inch)
19. R1D1 Very Hi-res Repeat Corrosion 10 in = 100 ft
19.1 Integration Summary
19.2 Composite Summary
19.3 Log (LBV1_USI Corrosion 9.625inch)
20. R1D1 Very Hi-res Repeat Corrosion 10 in = 100 ft
20.1 Integration Summary
20.2 Composite Summary
20.3 Log (LBV1_USI Corrosion 9.625inch)
21. XYZ (USI Fluid Acoustic Slowness vs Depth)
22. XYZ (USI Theoretical Acoustic impedance of mud vs Depth)
23. Tail

Well Sketch





Borehole Size/Casing/Tubing Record

Bit						
Bit Size (in)	17.5	12.25				
Top Driller (ft)	0	1046				
Top Logger (ft)	0	1046				
Bottom Driller (ft)	1046	7344				
Bottom Logger (ft)	1046	7344				
Casing						
Size (in)	13.375	9.625				
Weight (lbm/ft)	54.5	47				
Inner Diameter (in)	12.615	8.681				
Grade	K55	N80				
Top Driller (ft)	0	0				
Top Logger (ft)	0	0				
Bottom Driller (ft)	1046	7344				
Bottom Logger (ft)	1046	7344				

Remarks and Equipment Summary

R1D1: Toolstring

Equip name	Length	MP name	Offset
LEH-QT:2867	**59.39**	Red	
LEH-QT:2867			
DTC-H	**56.47**	**CTEM**	**55.57**
ECH-KC		**HV**	**0.00**
DTC-H		**TelStatus**	**53.47**
		ToolStatus	**53.47**
HGNS-H:3923	**53.47**	**Temperature**	**53.44**
HGNH:4819		**GR**	**52.73**
NPV-N			
NSR-F:5002			
HGNS-H:3			



R1D1: Remarks

Logging objectives: Cement and corrosion evaluation
USIT logged in 10 deg/1.5 inch, logging speed 2800-3000 fph, repeated hi-res in 10 deg/0.6 inch, speed 1000 fph
Top of sand at 7258 ft, logged from 7256 ft to ~60 ft under 0 psi surface pressure. Recorded separate pass up to ground level.
Rig: Ensign 342
Toolstring ran as per toolsketch.
Two centralizers on USIS and two CME-Y used to centralize ultrasonic tool.
Thank you for choosing Schlumberger!

HGNS-H:3
923
HACCZ-H:
3923
HMCA-H



CNL Porosity 46.4
HMCA 44.06
HGNS 44.06
Accelerometer 0.00

AH-184[4] 44.06

AH-184[3]:2985 42.06

DSLT-H:8236 40.06
ECH-KH:8
678
DSLC-H:82
36
SLS-E:120
6

CBL 3ft 27.59
Upper-Near 27.59
VDL 5ft 26.59
Upper-Far 26.59
Delta-T 25.22
Lower-Far 23.84
Lower-Near 22.84
SLS-E 19.42

AH-184[2]:2882 19.42

AH-184[1]:6735 17.42

USIT-E:1764 15.42
ECH-MFA:
1764
USAC-A:1
764
USIS-A:27
20
USSC-B
USRS-C:84
0
USI-SENS
OR:3349



Lengths are in ft
Maximum Outer Diameter = 6.690 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO

Job Event Summary

Event	Time	Duration	Interval	Remark
Run 1				Apr-05-2016 09:18
Log[1]:Down	Apr-05-2016 09:34	01:53:58	101.69 - 7255.94 ft	FPM
Log[2]:Up	Apr-05-2016 10:30	00:05:40	7260.42 - 7030.72 ft	Repeat Pass at TD 0 Psi
Log[3]:Up	Apr-05-2016 10:39	00:07:08	7256.38 - 6940.93 ft	Main Pass #1
Log[4]:Up	Apr-05-2016 10:49	00:05:23	7230.08 - 7138.31 ft	Very Hi-Res Repeat 0 Psi
Log[5]:Up	Apr-05-2016 10:55	02:22:17	7058.76 - 59.1 ft	Main Pass #2
Log[6]:Up	Apr-05-2016 13:39	00:02:47	4578.2 - 4534.85 ft	Very Hi-Res Repeat 0 Psi
Log[7]:Up	Apr-05-2016 13:45	00:05:21	4251.57 - 4166.36 ft	Very Hi-Res Repeat 0 Psi
Log[8]:Up	Apr-05-2016 13:54	00:07:55	3712.31 - 3586.28 ft	Very Hi-Res Repeat 0 Psi
Log[9]:Up	Apr-05-2016 14:15	00:12:19	1453.92 - 1251.76 ft	Very Hi-Res Repeat 0 Psi
Log[10]:Up	Apr-05-2016 14:30	00:03:24	840.92 - 783.97 ft	Very Hi-Res Repeat 0 Psi
Run 2				Apr-05-2016 15:00
Log[1]:Up	Apr-05-2016 15:04	00:04:56	206.15 - 25.25 ft	Surface Pass 0 Psi
Log[2]:Up	Apr-05-2016 15:10	00:04:47	84.25 - 21.42 ft	Very Hi-Res Repeat 0 Psi
Log[5]:Up	Apr-05-2016 15:18	00:01:44	49.03 - 20.94 ft	Very Hi-Res Repeat 0 Psi

USIT - Fluid Properties Measurement

Run Name	Pass Name	Start Depth(ft)	Stop Depth(ft)
Run 1	Log[5]:Up	7058.76	59.1

Fluid Velocity = "Automatic".
CFVL equals DFSL channel

Start Depth(ft)	Stop Depth(ft)	Start Value(us/ft)	End Value(us/ft)

Mud Impedance = "FreePipe Norm.".
Free Pipe normalization zone is : 30.69m(100.68ft) to 42.94m(140.88ft)
MUD_N_FRP = 1.10
DFD = 1.08g/cm3(9.00lbm/gal)
CZMD median computed in free pipe normalization interval = 1.81 MRayl

Start Depth(ft)	Stop Depth(ft)	Start Value(Mrayl)	End Value(Mrayl)

Composite 1

Main Pass 5 in = 100 ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Computation	Description	Version
CEVAL	Sonic Cement Evaluation Computation Ensemble provides common Parameters and Channels	6.1.58882.3100
Cementation	Cementation Computation Application	6.1.58882.3100

SoftwareVersion_Tool	SoftwareVersion_Run Version	SoftwareVersion_Build Version
WAFE-SEC	Synergy SV451EC version 9.10	Synergy SV451EC version 9.10
WAFE-FEC	Synergy SV451EC version 9.10	Synergy SV451EC version 9.10
WAFE-TMDI	Synergy SV451EC version 46.19	Synergy SV451EC version 46.19

Tool Elements	Description	Software Version	Firmware Version
HGNS-H	HILT Gamma-Ray and Neutron Sonde, 150 degC	6.1.58882.3100	2.0

SLS-E	Sonic Logging Sonde E supports 3'-5'BHC DT and CBL/VDL	6.1.58882.3100	4.0
USI-SENSOR	USIT Transducer Element	6.1.58882.3100	DSP: v1.82

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[3]:Up	Up	6940.93 ft	7256.38 ft	05-Apr-2016 10:39:42 AM	05-Apr-2016 10:46:50 AM	ON	0.00 ft	Yes
R1D1	Log[5]:Up	Up	59.10 ft	7058.76 ft	05-Apr-2016 10:55:54 AM	05-Apr-2016 1:18:12 PM	ON	0.18 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

Composite 1:S002

Description: USI VDL Cement Format: Log (LBV1_USI-VDL (DSLT) Cement 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:55:41

TIME_1900 - Time Marked every 60.00 (s)




50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
220
230
240
250
260
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
COLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
ECGR
ECCC_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
CCLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
700
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
AIMX
BI


IRAV_RF
RMN_RF
AIAV
COLU
ERAV_RF
ERAV_RF
AIMN
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920


ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
BI
COLU
ERAV_RF
ERAV_RF
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140


1150
1160
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
1170
IRMN_RF
IRMX_RF
AIMX
1180
IRAV_RF
IRMN_RF
AIAV
1190
COLU
ERAV_RF
ERAV_RF
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360


1370
1380
1390
1400
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
BI
AIAV
AIMN
COLU
ERAV_RF
ERAV_RF
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580


1590
1600
1610
1620
1630
1640
ECGR
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
BI
AIAV
AIMN
COLU
ERAV_RF
ERAV_RF


1810
1820
1830
1840
1850
1860
1870
1880
ECGR
ECGE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
B
1900
1910
COLU
ERAV_RF
ERAV_RF
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020


2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
AIMX
2140
IRAV_RF
IRMN_RF
AIAV
2150
COLU
ERAV_RF
ERAV_RF
AIMN
2160
2170
2180
2190
2200
2210
2220
2230
2240


2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2380
2390
2400
2410
2420
2430
2440
2450
2460
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
CCLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
BI
2620
2630
COLU
ERAV_RF
ERAV_RF
2640
2650
2660
2670
2680


2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
2890
2900
ECGR
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
COLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100
3110
3120
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
CCLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3330
3340
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
AIMX
BI


IRAV_RF
IRMN_RF
AIAV
AIMN
COLU
ERAV_RF
ERAV_RF
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560


ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
CCLU
ERAV_RF
ERAV_RF
B
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780


3790
3800
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
AIMX
3820
IRAV_RF
IRMN_RF
AIAV
3830
COLU
ERAV_RF
ERAV_RF
AIMN
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000


4010
4020
4030
4040
ECGR
4050
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
AIMX
4060
IRAV_RF
IRMN_RF
AIAV
4070
COLU
ERAV_RF
ERAV_RF
AIMN
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220


4230
4240
4250
4260
4270
4280
ECGR
ECOE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
RMN_RF
4300
AIMX
AIAV
AIMN
BI
4310
CCLU
ERAV_RF
ERAV_RF
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440


4450
4460
4470
4480
4490
4500
4510
4520
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
BI
4540
4550
AIAV
COLU
ERAV_RF
ERAV_RF
AIMN
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660


4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
4870
4880
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
CCLU
ERAV_RF
ERAV_RF
AIAV
AIMN
BI


4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
ECGR
5010
CCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
5020
IRAV_RF
IRMN_RF
5030
COLU
ERAV_RF
ERAV_RF
AIAV
AIMN
BI
5040
5050
5060
5070
5080
5090
5100


5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260
5270
5280
5290
5300
5310
5320
ECGR
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
COLU
ERAV_RF
ERAV_RF
AIAV
AIMN
AIMX
BI


5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
ECGR
5490
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
5500
IRAV_RF
IRMN_RF
AIAV
5510
CCLU
ERAV_RF
AIMN
5520
5530
5540


5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
CCLU
ERAV_RF
ERAV_RF
AIAV
AIMN
BI


5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5980
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
AIMX
BI


IRAV_RF
IRMN_RF
AIAV
COLU
ERAV_RF
ERMN_RF
AIMN
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200


ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
AIMX
IRAV_RF
RMN_RF
AIAV
COLU
ERAV_RF
ERAV_RF
AIMN
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420


6430
6440
ECGR
6450
RF
RMX_RF
RAV_RF
BI
RMN_RF
RMX_RF
6460
AIMX
RAV_RF
RMN_RF
AIAV
6470
COLU
ERAV_RF
ERAV_RF
AIMN
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640


6650
6660
6670
6680
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
6700
IRMN_RF
IRMX_RF
AIMX
IRAV_RF
IRMN_RF
AIAV
6710
COLU
ERAV_RF
ERAV_RF
AIMN
6720
6730
6740
6750
6760
6770
6780
6790
6800
6810
6820
6830
6840
6850
6860


6870
6880
6890
6900
6910
6920
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
AIMX
6940
IRAV_RF
IRMN_RF
AIAV
6950
CCLU
ERAV_RF
ERAV_RF
AIMN
6960
6970
6980
6990
7000
7010
7020
7030
7040
7050
7060
7070
7080



Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]

ERAV_IRAV
IRAV_LHF1
LHF1_ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

ERAV_RHF1
IRAV_ERAV
RHF1_IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Absent 1.000 2.500 4.000 5.500 7.000
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Acoustic Impedance Minimum (AIMN) USIT-E[1]
-1 Mrayl 9

Acoustic Impedance Average (AIAV) USIT-E[1]
-1 Mrayl 9

Acoustic

Absent 0.300 3.581 5.054 6.527 8.000
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)

Bonded
Gas
Liquid
Micro-debonding

Bond Index (BI) DSLT-H[1]
1 0

Min Amplitude Max
Sonic VDL Curve DSLT-H[1]
200 us 1200



Description: USI VDL Cement Format: Log (LBV1_USI-VDL (DSLT) Cement 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:55:41

Channel Processing Parameters

R1D1: Parameters

Parameter	Description	Tool	Value	Unit
AMSG	Auxiliary Minimum Sliding Gate	DSLT-H	140	us
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BERJ	Bad Echo Rejection	USIT-E	On	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BILI	Bond Index Level for Zone Isolation	DSLT-H	0.8	
BS	Bit Size	WLSESSION	Depth Zoned	in
CASING_PRATIO	Casing Poisson Ratio	USIT-E	Standard Poisson Ratio	
CBLG	CBL Gate Width	DSLT-H	45	us
CBLO	Casing Bottom (Logger)	WLSESSION	7344	ft
CBRA	CBL LQC Reference Amplitude in Free Pipe	DSLT-H	52	mV
CDEN	Cement Density	HGNS-H	2	g/cm3
CMCF	CBL Cement Type Compensation Factor	DSLT-H	1	
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
DETE	Delta-T Detection	DSLT-H	E1	
DFD	Drilling Fluid Density	Borehole	9	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	195	us/ft
FCF	CBL Fluid Compensation Factor	DSLT-H	0.89	
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
GOBO_CURR	Good Bond in Arbitrary Cement	DSLT-H	4.78	mV
GR_MULTIPLIER	Gamma Ray Multiplier	HGNS-H	1	
HEMA	Hematite Presence Flag	Borehole	No	

ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MAHTR	Manual High Threshold Reference for first arrival detection	DSLT-H	120	
MATT_CURR	Maximum Attenuation in Arbitrary Cement	DSLT-H	9.3	dB/ft
MCI	Minimum Cemented Interval for Isolation	DSLT-H	Depth Zoned	ft
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MNHTR	Minimum High Threshold Reference for first arrival detection	DSLT-H	100	
MSA	Minimum Sonic Amplitude	DSLT-H	2.63	mV
MSA_CURR	Minimum Sonic Amplitude in Arbitrary Cement	DSLT-H	2.63	mV
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1.1	
MUD_N_THE	Theoretical Mud Normalization Factor	USIT-E	1	
NMSG	Near Minimum Sliding Gate	DSLT-H	322	us
NMXG	Near Maximum Sliding Gate	DSLT-H	940	us
NUMP	Number of Detection Passes	DSLT-H	2	
OPLEV	USIT Remove Flagged Data Level	USIT-E	OPT2	
RCOD	Reference Calibrator Outer Diameter	USIT-E	7	in
RCSO	Reference Calibrator Standoff	USIT-E	1.378	in
RCTH	Reference Calibrator Thickness	USIT-E	0.295	in
SDNV	Number of Vertical Samples used for Micro-debonding Computation	USIT-E	5	
SDTHOR	Acoustic Impedance STD Horizontal Threshold for Micro-debonding	USIT-E	0.5	Mrayl
SDTVER	Acoustic Impedance STD Vertical Threshold for Micro-debonding	USIT-E	0.3	Mrayl
SFAF	Sonic Formation Attenuation Factor	DSLT-H	3.25	dB/ft
SGAD	Sliding Gate Status	DSLT-H	Off	
SGCL	Sliding Gate Closing Delta-T	DSLT-H	130	us/ft
SGCW	Sliding Gate Closing Width	DSLT-H	25	us
SGDT	Sliding Gate Delta-T	DSLT-H	57	us/ft
SGW	Sliding Gate Width	DSLT-H	110	us
SLEV	Signal Level for AGC	DSLT-H	5000	mV
SOCN	Standoff Distance	HGNS-H	0.125	in
SOCO	Standoff Correction Option	HGNS-H	No	
TCUB	T^3 Processing Level	USIT-E	Loop	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	130	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	70	%
HISC	Tool Position: Centered or Eccentered	HGNS-H	Eccentered	
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
THDP	Thickness Detection Policy	USIT-E	Fundamental	
VCAS	Ultrasonic Transversal Velocity in Casing	USIT-E	51.4	us/ft
VDLG	VDL Manual Gain	DSLT-H	5	
ZCAS	Acoustic Impedance of Casing	USIT-E	46.25	Mrayl
ZCMT	Acoustic Impedance of Cement	DSLT-H	6.8	Mrayl
ZCMT_NEAT	Acoustic Impedance of Cement in Neat Cement	DSLT-H	6.8	Mrayl
ZINI	Initial Estimate of Cement Impedance	USIT-E	-1	Mrayl
ZMUD	Acoustic Impedance of Mud	Borehole	1.8	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl

ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

R1D1Depth Zoned Parameters

Parameter	Value	Start (ft)	Stop (ft)
BS	17.5	6.5	1046
BS	12.25	1046	7256
MCI	21.68	6.5	1046
MCI	14.81	1046	7256

All depth are actual.

Tool Control Parameters

R1D1: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
DDEL	Digitizing Delay	DSLT-H	0	us
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
DOT(DOS)	Distance between Opposite Transducer Faces	USIT-E	4.874	in
MODE	DSLT Acquisition Mode	DSLT-H	CBL	
RATE	DSLT Firing Rate	DSLT-H	15 Hz	
DTFS	DSLT Telemetry Frame Size	DSLT-H	536	
DWCO	Digitizer Word Count	DSLT-H	250	
EMXV	EMEX Voltage	USIT-E	Time Zoned	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	On	
SDTH	Switch Down Threshold	DSLT-H	20000	
SGAI	Selectable Acquisition Gain	DSLT-H	x1	
SUTH	Switch Up Threshold	DSLT-H	1000	
TMUC	Type of Mud	USIT-E	BRI	
UACLV_PERM	Ultrasonic ACLV Permanent	USIT-E	No	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 1.5 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	7250	ft
USSP	Ultrasonic Service	USIT-E	USI	
VRES	Vertical Resolution	USIT-E	1.5 in	
WINB	Window Begin Time	USIT-E	20	us
WINE	Window End Time	USIT-E	100	us
WMOD	Waveform Firing Mode	DSLT-H	Full	

R1D1Time Zoned Parameters

Pass Log[3]:Up

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
EMXV	40	05-Apr-2016 10:39:49	05-Apr-2016 10:46:50	7256.26	6983.98

Pass Log[5]:Up

EMXV	40	05-Apr-2016 10:55:54	05-Apr-2016 13:15:50	6984.52	113.17
EMXV	60	05-Apr-2016 13:15:50	05-Apr-2016 13:18:12	113.17	59.01

All depth are at tool zero.

All depth are at tool zero.

Composite 1

Main Pass 5 IN = 100 FT

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[3]:Up	Up	6940.93 ft	7256.38 ft	05-Apr-2016 10:39:42 AM	05-Apr-2016 10:46:50 AM	ON	0.00 ft	Yes
R1D1	Log[5]:Up	Up	59.10 ft	7058.76 ft	05-Apr-2016 10:55:54 AM	05-Apr-2016 1:18:12 PM	ON	0.18 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

Composite 1:S002

Description: USI Composite Format: Log (LBV1_USI Composite 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth

Creation Date: 05-Apr-2016 16:56:23

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :

2 - UFLG 2 Value within [1.5 - 2.5] - :

3 - UFLG 3 Value within [2.5 - 3.5] - :

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5

Motor Revolution Speed (RSAV)

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]

USIT Processing Flags

Absent -4.799 -2.799 -0.800
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1] (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF)

ERAV | IRAV | ERAV-IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF)

Minimum of Unflagged Internal Radii (IRMN_RF)

Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF)

Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness

Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT - Acoustic Impedance

Ratio of Cement Measurements to Total (CEMR) USIT-E[1]
1 0

Micro-debonding Ratio (MDR) USIT-E[1]
1 0

Ratio of Gas Measurements to Total (GASR) USIT-E[1]
1 0

Bonded | Gas | Liquid | Micro-debonding

Bond Index (BI)

Absent 3.090 5.054 7.018
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Absent 2.599 4.563 6.527
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBO


USIT-E[1]
6 c/s 8
(UFLG[0]) USIT-E[1]
1 5
USIT-E[1]
0 dB 75
USIT-E[1]
5 in 4
USIT-E[1]
4 in 5
(IRBKM_RF) USIT-E[1]
(in)
USIT-E[1]
0.1 in 0.6
(THBKM_RF) USIT-E[1]
(in)
(AIBK) USIT-E[1]
(Mrayl)
DSLT-H[1]
1 0
ND_IMG) USIT-E[1]
(Mrayl)
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240


250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460


470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680


690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900


910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
RSAV
ECCE_RF
COLU
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340


1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560


1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780


1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
1940
1950
1960
1970
1980
1990
2000
RSAV
ECCE_RF
COLU
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150
2160
2170
2180
2190
2200
2210
2220


2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440


2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
2610
2620
2630
2640
2650
2660


2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
RSAV
ECCE_RF
COLU
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100


3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320


3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540


3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760


3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
RSAV
ECCE_RF
COLU
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200


4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420


4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570
4580
4590
4600
4610
4620
4630
4640


4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
RSAV
ECCE_RF
CCLU
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080


5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260
5270
5280
5290
5300


5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
5490
5500
5510
5520


5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
RSAV
AWMX_RF
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
THMX_RF
THAV_RF
BI


ECCE_RF
CCLU
AWAV_RF
AWMN_RF
IRAV_RF
ERAV_RF
IRAV_RF
ERAV_RF
THNO
THMN_RF
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960


5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180


6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400


6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620


6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
6780
6790
6800
6810
6820
6830
6840
RSAV
ECCE_RF
COLU
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


6850
6860
6870
6880
6890
6900
6910
6920
6930
6940
6950
6960
6970
6980
6990
7000
7010
7020
7030
7040
7050
7060
Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice


7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170
7180
7190
7200
7210
7220
7230
7240
7250
Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10
Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing
Absent -4.799 -2.799 -0.800
Explicit Normalization
USIT -
ERAV
ERAV-IRAV
IRAV
IRAV
ERAV
IRAV-ERAV
Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT -
Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6
Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT -
Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT -
Ratio of Cement Measurements to Total (CEMR) USIT-E[1]
1 0
Absent 3.090 5.054 7.018
Custom Normalization
USIT -

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Flags (UFLG) USIT-E[1]

USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5

Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1] (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]
0 dB 75

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5

Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1] (in)

Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E[1]
0.1 in 0.6

Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1] (in)

Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Micro-debonding Ratio (MDR) USIT-E[1]
1 0

Ratio of Gas Measurements to Total (GASR) USIT-E[1]
1 0

Bonded

Gas

Liquid

Micro-debonding

Bond Index (BI) DSLT-H[1]
1 0

Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Absent 2.599 4.563 6.527

Custom Normalization

USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Composite 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:56:23

Composite 1

Cement Log 2 IN = 100 FT

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[3]:Up	Up	6940.93 ft	7256.38 ft	05-Apr-2016 10:39:42 AM	05-Apr-2016 10:46:50 AM	ON	0.00 ft	Yes
R1D1	Log[5]:Up	Up	59.10 ft	7058.76 ft	05-Apr-2016 10:55:54 AM	05-Apr-2016 1:18:12 PM	ON	0.18 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B
Composite 1:S002

Description: USI Cement Format: Log (LBV1_USI Cement 9.625inch) Index Scale: 2 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:57:18

TIME_1900 - Time Marked every 60.00 (s)

ERAV_IRAV ERAV_PHF1


ERAV_IRAV
ERAV_RHF1
IRAV_LHF1
IRAV_ERAV
LHF1_ERAV
RHF1_IRAV
Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4
Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5
Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5
Gamma Ray (ECGR) HGNS[1]
0 gAPI 150
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5
Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 1
Absent 0.500 1.500 2.500 3.500 4.500 5.500 6.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)
Acoustic Impedance Minimum (AIMN) USIT-E[1]
-1 Mrayl 9
Acoustic Impedance Average (AIAV) USIT-E[1]
-1 Mrayl 9
Acoustic Impedance Maximum (AIMX) USIT-E[1]
-1 Mrayl 9
Bonded
Gas
Liquid
Micro-debonding
Absent -500.000 2.599 3.581 4.563 5.545 6.527 7.509
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)
50
100
150
200
250


300
350
400
450
500
550
600
650
700
750
800


850
900
950
1000
1050
1100
1150
1200
1250
1300
1350
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
COLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN


1400
1450
1500
1550
1600
1650
1700
1750
1800
1850
1900


1950
2000
2050
2100
2150
2200
2250
2300
2350
2400
2450
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
CCLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN


2500
2550
2600
2650
2700
2750
2800
2850
2900
2950
3000


3050
3100
3150
3200
3250
3300
3350
3400
3450
3500
3550
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
AIMX


IRAV_RF
IRAV_RF
AIAV
CCLU
ERAV_RF
ERAV_RF
AIMN
3600
3650
3700
3750
3800
3850
3900
3950
4000
4050
4100


4150
4200
4250
4300
4350
4400
4450
4500
4550
4600
4650


4700
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
AIMX
4750
IRAV_RF
IRAV_RF
AIAV
CCLU
ERAV_RF
ERAV_RF
AIMN
4800
4850
4900
4950
5000
5050
5100
5150
5200


5250
5300
5350
5400
5450
5500
5550
5600
5650
5700
5750


5800
5850
5900
5950
6000
6050
6100
6150
6200
6250
6300
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
COLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN


6350
6400
6450
6500
6550
6600
6650
6700
6750
6800
6850


6900
6950
7000
7050
7100
7150
7200
7250
Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
CCLU
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10
Gamma Ray (ECGR) HGNS[1]
0 gAPI 150
Amplitude of Eccentering for Unflagged Waves (ECCE_RF)
ERAV_IRAV
IRAV_LHF1
LHF1_ERAV
Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4
Median Internal Radius of Casing Corrected for Eccentering
ERAV_RHF1
IRAV_ERAV
RHF1_IRAV
Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5
Median Internal Radius of Casing Corrected for Eccentering
Absent 0.500 1.500 2.500 3.500 4.500 5.500 6.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)
Acoustic Impedance Minimum (AIMN) USIT-E[1]
-1 Mrayl 9
Acoustic Impedance Average (AIAV) USIT-E[1]
-1 Mrayl 9
Acoustic Impedance Maximum (AIMX) USIT-E[1]
-1 Mrayl 9
Bonded
Gas
Liquid
Micro-debondin g
Absent -500.000 2.599 3.581 4.563 5.545 6.527 7.509
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)

USIT-E[1]
0 in 1

Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Cement Format: Log (LBV1_USI Cement 9.625inch) Index Scale: 2 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:57:18

Composite 1

Corrosion 5 in = 100 ft

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[3]:Up	Up	6940.93 ft	7256.38 ft	05-Apr-2016 10:39:42 AM	05-Apr-2016 10:46:50 AM	ON	0.00 ft	Yes
R1D1	Log[5]:Up	Up	59.10 ft	7058.76 ft	05-Apr-2016 10:55:54 AM	05-Apr-2016 1:18:12 PM	ON	0.18 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B Composite 1:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:57:55

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error
Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

Absent -5.200 -3.600 -2.000 -0.400

Explicit Normalization

USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1]

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6

Median Internal

Median Internal


Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10
Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5
Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8
Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]
USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5
(dB)
Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75
Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]
0 dB 75
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1]
(in)
Internal Radius Averaged Value (IRAV) USIT-E[1]
4 in 5
Internal Radius Maximum Value (IRMX) USIT-E[1]
4 in 5
Internal Radius Minimum Value (IRMN) USIT-E[1]
4 in 5
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1]
(in)
Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6
Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E[1]
0.1 in 0.6
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200


210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420


430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640


650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860


870
880
890
900
910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080


1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300


1310
1320
1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520


1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740


1750
1760
1770
1780
1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
1940
1950
1960


1970
1980
1990
2000
2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150
2160
2170
2180


2190
2200
2210
2220
2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400


2410
2420
2430
2440
2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
2610
2620


2630
2640
2650
2660
2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840


2850
2860
2870
2880
2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060


3070
3080
3090
3100
3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280


3290
3300
3310
3320
3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500


3510
3520
3530
3540
3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720


3730
3740
3750
3760
3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940


3950
3960
3970
3980
3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160


4170
4180
4190
4200
4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350
4360
4370
4380


4390
4400
4410
4420
4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570
4580
4590
4600


4610
4620
4630
4640
4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820


4830
4840
4850
4860
4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040


5050
5060
5070
5080
5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260


5270
5280
5290
5300
5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480


5490
5500
5510
5520
5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700


5710
5720
5730
5740
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920


5930
5940
5950
5960
5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140


6150
6160
6170
6180
6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360


6370
6380
6390
6400
6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580


6590
6600
6610
6620
6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
6780
6790
6800


6810
6820
6830
6840
6850
6860
6870
6880
6890
6900
6910
6920
6930
6940
6950
6960
6970
6980
6990
7000
7010
7020


7030
7040
7050
7060
7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170
7180
7190
7200
7210
7220
7230
7240



Casing Collar Locator Ultrasonic (CCLU) USIT-E[1]
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]

USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1] (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1] (in)

Internal Radius Averaged Value (IRAV) USIT-E[1]
4 in 5

Internal Radius Maximum Value (IRMX) USIT-E[1]
4 in 5

Internal Radius Minimum Value (IRMN) USIT-E[1]
4 in 5

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1] (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E[1]
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:57:55

Composite 1

USI Compressed Goodwin

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[3]:Up	Up	6940.93 ft	7256.38 ft	05-Apr-2016 10:39:42 AM	05-Apr-2016 10:46:50 AM	ON	0.00 ft	Yes
R1D1	Log[5]:Up	Up	59.10 ft	7058.76 ft	05-Apr-2016 10:55:54 AM	05-Apr-2016 1:18:12 PM	ON	0.18 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

Composite 1:S002

Description: USI Goodwin Format: Log (Import of USI Goodwin) Index Scale: 0.1 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:58:38

TIME_1900 - Time Marked every 60.00 (s)

Minimum Acoustic Impedance 1 (MIN_AI1) USIT-E[1]	Minimum Acoustic Impedance 3 (MIN_AI3) USIT-E[1]	Minimum Acoustic Impedance 5 (MIN_AI5) USIT-E[1]	Minimum Acoustic Impedance 7 (MIN_AI7) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10
Maximum Acoustic Impedance 1 (MAX_AI1) USIT-E[1]	Maximum Acoustic Impedance 3 (MAX_AI3) USIT-E[1]	Maximum Acoustic Impedance 5 (MAX_AI5) USIT-E[1]	Maximum Acoustic Impedance 7 (MAX_AI7) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10
Average Acoustic Impedance 1 (AV_AI1) USIT-E[1]	Average Acoustic Impedance 3 (AV_AI3) USIT-E[1]	Average Acoustic Impedance 5 (AV_AI5) USIT-E[1]	Average Acoustic Impedance 7 (AV_AI7) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10

Minimum Acoustic Impedance 2 (MIN_AI2) USIT-E[1]	Minimum Acoustic Impedance 4 (MIN_AI4) USIT-E[1]	Minimum Acoustic Impedance 6 (MIN_AI6) USIT-E[1]	Minimum Acoustic Impedance 8 (MIN_AI8) USIT-E[1]	Minimum Acoustic Impedance 9 (MIN_AI9) USIT-E[1]	Acoustic Impedance Minimum (AIMN) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	-1 Mrayl 9
Maximum Acoustic Impedance 2 (MAX_AI2) USIT-E[1]	Maximum Acoustic Impedance 4 (MAX_AI4) USIT-E[1]	Maximum Acoustic Impedance 6 (MAX_AI6) USIT-E[1]	Maximum Acoustic Impedance 8 (MAX_AI8) USIT-E[1]	Maximum Acoustic Impedance 9 (MAX_AI9) USIT-E[1]	Acoustic Impedance Maximum (AIMX) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	-1 Mrayl 9
Average Acoustic Impedance 2 (AV_AI2) USIT-E[1]	Average Acoustic Impedance 4 (AV_AI4) USIT-E[1]	Average Acoustic Impedance 6 (AV_AI6) USIT-E[1]	Average Acoustic Impedance 8 (AV_AI8) USIT-E[1]	Average Acoustic Impedance 9 (AV_AI9) USIT-E[1]	Acoustic Impedance Average (AIAV) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	-1 Mrayl 9

GR
0 gAPI 150

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Amplitude of Eccentering (ECCE) USIT-E[1]
0 in 0.5

Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Bonded
Micro-Debonding
Liquid
Gas

-1000.000 3.090 5.054 7.018
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)





GR
0 gAPI 150

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Amplitude of Eccentering (ECCE) USIT-E[1]
0 in 0.5

Minimum Acoustic Impedance 1 (MIN_AI1) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 3 (MIN_AI3) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 5 (MIN_AI5) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 7 (MIN_AI7) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 9 (MIN_AI9) USIT-E[1]
0 Mrayl 10

Acoustic Impedance Minimum (AIMN) USIT-E[1]
-1 Mrayl 9

Maximum Acoustic Impedance 1 (MAX_AI1) USIT-E[1]
0 Mrayl 10

Maximum Acoustic Impedance 3 (MAX_AI3) USIT-E[1]
0 Mrayl 10

Maximum Acoustic Impedance 5 (MAX_AI5) USIT-E[1]
0 Mrayl 10

Maximum Acoustic Impedance 7 (MAX_AI7) USIT-E[1]
0 Mrayl 10

Maximum Acoustic Impedance 9 (MAX_AI9) USIT-E[1]
0 Mrayl 10

Acoustic Impedance Maximum (AIMX) USIT-E[1]
-1 Mrayl 9

Average Acoustic Impedance 1 (AV_AI1) USIT-E[1]
0 Mrayl 10

Average Acoustic Impedance 3 (AV_AI3) USIT-E[1]
0 Mrayl 10

Average Acoustic Impedance 5 (AV_AI5) USIT-E[1]
0 Mrayl 10

Average Acoustic Impedance 7 (AV_AI7) USIT-E[1]
0 Mrayl 10

Average Acoustic Impedance 9 (AV_AI9) USIT-E[1]
0 Mrayl 10

Acoustic Impedance Average (AIAV) USIT-E[1]
-1 Mrayl 9

Minimum Acoustic Impedance 2 (MIN_AI2) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 4 (MIN_AI4) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 6 (MIN_AI6) USIT-E[1]
0 Mrayl 10

Minimum Acoustic Impedance 8 (MIN_AI8) USIT-E[1]
0 Mrayl 10

Maximum Acoustic Impedance 2 (MAX_AI2) USIT-E[1]

Maximum Acoustic Impedance 4 (MAX_AI4) USIT-E[1]

Maximum Acoustic Impedance 6 (MAX_AI6) USIT-E[1]

Maximum Acoustic Impedance 8 (MAX_AI8) USIT-E[1]

0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10
Average Acoustic Impedance 2 (AV_AI2) USIT-E[1]	Average Acoustic Impedance 4 (AV_AI4) USIT-E[1]	Average Acoustic Impedance 6 (AV_AI6) USIT-E[1]	Average Acoustic Impedance 8 (AV_AI8) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Goodwin Format: Log (Import of USI Goodwin) Index Scale: 0.1 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:58:38

R1D1

Repeat Pass 5 IN = 100 FT

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[2]:Up	Up	7030.73 ft	7260.43 ft	05-Apr-2016 10:30:56 AM	05-Apr-2016 10:36:37 AM	ON	7.08 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

R1D1: Log[2]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Composite 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 05-Apr-2016 16:58:43

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

ERAV | IRAV

ERAV-IRAV | ERAV

IRAV | IRAV-ERAV

Absent -4.799 -2.799 -0.800

Explicit Normalization

USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Median of Unflagged External Radii (ERAV_RF) USIT-E 5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E 4 in 5

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E 0.1 in 0.6

Ratio of Cement Measurements to Total (CEMR) USIT-E 1 0

Micro-debonding Ratio (MDR) USIT-E 1 0

Ratio of Gas Measurements to Total (GASR) USIT-E 1 0

Absent 3.090 5.054 7.018

Custom Normalization

USIT - Acoustic Impedance (AIBK) USIT-E (Mrayl)

Absent 2.599 4.563 6.527

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E 0 dB 75

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E 5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E 4 in 5

Nominal Casing Thickness (THNO) USIT-E 0.1 in 0.6

Absent -0.051 -0.012 0.028 0.068

Explicit

Casing Collar Locator Ultrasonic (CCLU) USIT-E -30 in 10

Absent 1.500 3.500

Amplitude of Eccentering

Average of Unflagged Wave

Absent -0.051 -0.012 0.028 0.068

Median of Unflagged Casing

Maximum of

Maximum of


Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5
Motor Revolution Speed (RSAV) USIT-E
6 c/s 8
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5
Wave Amplitude (AWAV_RF) USIT-E
0 dB 75
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75
Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4
Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)
Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)
Absent
1.500
3.500
5.500
7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E
(Mrayl)
Bonded
Gas
Liquid
Micro-debonding
Bond Index (BI) DSLT-H
1 0
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E
(Mrayl)
7010
7020
7030
7040
7050
7060
7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170



Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -4.799 -2.799 -0.800
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E (Mrayl)

Ratio of Cement Measurements to Total (CEMR) USIT-E
1 0

Micro-debonding Ratio (MDR) USIT-E
1 0

Ratio of Gas Measurements to Total (GASR) USIT-E
1 0

Bonded
Gas
Liquid
Micro-debonding

Bond Index (BI) DSLT-H
1 0

Absent 3.090 5.054 7.018
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E (Mrayl)

Absent 2.599 4.563 6.527
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E (Mrayl)

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

Description: USI Composite Format: Log (LBV1_USI Composite 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:43

R1D1

Very Hi-res Repeat Corrosion 10 in = 100 ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[10]:Up	Up	783.97 ft	840.93 ft	05-Apr-2016 2:30:48 PM	05-Apr-2016 2:34:12 PM	ON	2.83 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B
R1D1: Log[10]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:47

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6


0 in 0.5
Motor Revolution Speed (RSAV) USIT-E
6 c/s 8
Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6
790
800
810
820
830
840
Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10
Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5
Motor Revolution Speed (RSAV) USIT-E
6 c/s 8
Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5
Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)
Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75
Average of Unflagged Wave Amplitude (AWAV_RF)
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)
Internal Radius Averaged Value (IRAV) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
ERAV
ERAV-IRAV
IRAV
Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4
IRAV
ERAV
IRAV-ERAV
Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)
Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6
Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6
Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6
Maximum of Unflagged

USIT-E

0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E

0 dB 75

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E

5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E

4 in 5

Casing Thickness (THMX_RF) USIT-E

0.1 in 0.6

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E

5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E

4 in 5

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - : Pulse Origin Not Detected

3 - UFLG 3 Value within [2.5 - 3.5] - : WINLEN Error

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - : Casing Thickness Error

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - : Loop Processing Error

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:47

R1D1

Very Hi-res Repeat Corrosion 10 in = 100 ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[9]:Up	Up	1251.76 ft	1453.92 ft	05-Apr-2016 2:15:25 PM	05-Apr-2016 2:27:45 PM	ON	2.64 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

R1D1: Log[9]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:50

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - : Pulse Origin Not Detected

3 - UFLG 3 Value within [2.5 - 3.5] - : WINLEN Error

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - : Casing Thickness Error

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - : Loop Processing Error

Absent -5.200 -3.600 -2.000 -0.400

Explicit Normalization

USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E

ERAV IRAV

ERAV-IRAV ERAV

IRAV IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E

5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E

4 in 5

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E


Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10
Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5
Motor Revolution Speed (RSAV) USIT-E
6 c/s 8
Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5
(dB)
Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75
Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)
Internal Radius Averaged Value (IRAV) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)
0.1 in 0.6
Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6
Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6
1260
1270
1280
1290
1300
1310
1320


1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430



Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error
Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:50

Very Hi-res Repeat Corrosion 10 in = 100 ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[8]:Up	Up	3586.28 ft	3712.31 ft	05-Apr-2016 1:54:20 PM	05-Apr-2016 2:02:16 PM	ON	1.70 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

R1D1: Log[8]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:54

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error




3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700



Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:54

R1D1

Very Hi-res Repeat Corrosion 10 in = 100 ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[7]:Up	Up	4166.36 ft	4251.57 ft	05-Apr-2016 1:45:46 PM	05-Apr-2016 1:51:07 PM	ON	1.42 ft	Yes

All depths are referenced to toolstring zero

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B

R1D1: Log[7]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:58

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6





Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

USIT-E
5 in 4

USIT-E
4 in 5

USIT-E
0.1 in 0.6

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:58:58

R1D1

Very Hi-res Repeat Corrosion 10 in = 100 ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[6]:Up	Up	4534.85 ft	4578.20 ft	05-Apr-2016 1:39:00 PM	05-Apr-2016 1:41:48 PM	ON	1.60 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B
R1D1: Log[6]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:59:00

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Absent -5.200 -3.600 -2.000 -0.400

Explicit Normalization

USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave

ERAV IRAV
ERAV-IRAV ERAV
IRAV IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing

Median Internal Radius of Casing

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing

Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6



Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E

6 c/s 8

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

(IRAV_RF) USIT-E
5 in 4

(IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error
Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:59:00

R1D1

Very Hi-res Repeat Corrosion 10 in = 100 ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
R1D1	Log[4]:Up	Up	7138.31 ft	7230.08 ft	05-Apr-2016 10:49:13 AM	05-Apr-2016 10:54:36 AM	ON	0.00 ft	Yes

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:Porter 69B
R1D1: Log[4]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:59:03

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error
Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii

Median of Unflagged External Radii

Minimum of

Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6





Casing Collar Locator Ultrasonic (CCLU) USIT-E
-30 in 10

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 05-Apr-2016 16:59:03

XYZ

Company:Southern California Gas Company Well:Porter 69B
Composite 1:S002

Fluid Acoustic Slowness vs Depth

2D Cross Plot

Index Range: From 58.87 to 7256.50 ft



XYZ

Company:Southern California Gas Company Well:Porter 69B
Composite 1:S002

Theoretical Acoustic Impedance of Mud vs Depth

2D Cross Plot

Index Range: From 58.87 to 7256.50 ft

DEPTH-CZMD
DEPTH-AIBH (AIBH : Data Not Found)


DEPTH-AIBL (AIBL : Data Not Found)
DEPTH-AIBM (AIBM : Data Not Found)
AIBM (Mrayl)
AIBL (Mrayl)
AIBH (Mrayl)
Acoustic Impedance of Mu...-CZMD (Mrayl)
3.0
2.4
1.8
1.2
0.6
0.0
2.5
2.0
1.5
1.0
0.5
0
1520
3040
4560
6080
7600
Depth Index-DEPTH (ft)

Company:	Southern California Gas Company
Well:	Porter 69B
Field:	Aliso Canyon
County:	Los Angeles
State:	California

Schlumberger

Ultrasonic Imager

Gamma Ray - CCL

9-5/8" 47# casing