Schlumberger

Company: Southern California Gas Company

Well: PORTER 72A

Field: Aliso Canyon

County: Los Angeles State: California

Ultrasonic Imager

Gamma Ray - CCL

9-5/8" 47# casing

County:	Los Angeles
Field:	Aliso Canyon
Location:	From Station 84,
Well:	PORTER 72A
Company:	Southern California Gas Company

Location:			
From Station 84, 960' South & 705' West	Elev.:	K.B.	1932.50 ft
		G.L.	1909.00 ft
		D.F.	
Permanent Datum:	Ground Level	Elev.:	1909.00 f
Log Measured From:	Kelly Bushing	23.50 ft	above Perm.Datum
Drilling Measured From:	Kelly Bushing		

API Serial No.	Section:	Township:	Range:
037-24145	27	3N	16W

Logging Date		18-May-2016	
Run Number		One	
Depth Driller		6800.00 ft	
Schlumberger Depth		6796.00 ft	
Bottom Log Interval		6796.00 ft	
Top Log Interval		35.00 ft	
Casing Fluid Type		Water	
Salinity			
Density		9.3 lbm/gal	
Fluid Level		8.00 ft	
BIT/CASING/TUBING STRING			
Bit Size		15.00 in	
From		6899.00 ft	
To		7170.00 ft	
Casing/Tubing Size		5.5 in	
Weight		17 lbm/ft	
Grade		K55	
From		6816.00 ft	
To		7170.00 ft	
Max Recorded Temperatures			
Logger on Bottom	Time	18-May-2016 11:40:00	
Unit Number	Location:	3189 Ventura	
Recorded By		John Lopez	
Witnessed By		Mr Tom McMahon	

Disclaimer

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

Contents

1. Header
2. Disclaimer
3. Contents
4. Well Sketch
5. Borehole Size/Casing/Tubing Record
6. Remarks and Equipment Summary
7. Job Event Summary
8. USI Fluid Properties Measurement
9. Composite 1 Main Pass 5 in = 100 ft
   9.1 Integration Summary
   9.2 Software Version
   9.3 Composite Summary
   9.4 Log (LBV1_USI-VDL (DSLT) Cement 9.625inch)
   9.5 Parameter Listing
10. Composite 1 Main Pass 5 IN = 100 FT
   10.1 Integration Summary
   10.2 Composite Summary
   16.3 Log (LBV1_USI Corrosion 9.625inch)
17. One Very Hi-Res Repeat 10in=100ft
   17.1 Integration Summary
   17.2 Software Version
   17.3 Composite Summary
   17.4 Log (LBV1_USI Corrosion 9.625inch)
   17.5 Parameter Listing
18. One Very Hi-Res Repeat 10in=100ft
   18.1 Integration Summary
   18.2 Software Version
   18.3 Composite Summary
   18.4 Log (LBV1_USI Corrosion 9.625inch)
   18.5 Parameter Listing
19. One Very Hi-Res Repeat 10in=100ft
   19.1 Integration Summary
   19.2 Software Version
   19.3 Composite Summary

10.3 Log (LBV1_USI Composite 9.625inch)
11. Composite 1 Cement Log 2 IN = 100 FT
11.1 Integration Summary
11.2 Composite Summary
11.3 Log (LBV1_USI Cement 9.625inch)
12. Composite1
12.1 Integration Summary
12.2 Software Version
12.3 Composite Summary
12.4 Log (LBV1_USI Corrosion 9.625inch)
12.5 Parameter Listing
13. Composite 1 USI Compressed Goodwin
13.1 Integration Summary
13.2 Composite Summary
13.3 Log (Import of USI Goodwin)
14. One Very Hi-Res Repeat 10in=100ft at 600 khz
14.1 Integration Summary
14.2 Composite Summary
14.3 Log (LBV1_USI Corrosion 9.625inch)
15. One Very Hi-Res Repeat 10in=100ft
15.1 Integration Summary
15.2 Composite Summary
15.3 Log (LBV1_USI Corrosion 9.625inch)
16. One Very Hi-Res Repeat 10in=100ft
16.1 Integration Summary
16.2 Composite Summary
19.4 Log (LBV1_USI Corrosion 9.625inch)
19.5 Parameter Listing
20. One Very Hi-Res Repeat 10in=100ft
20.1 Integration Summary
20.2 Software Version
20.3 Composite Summary
20.4 Log (LBV1_USI Corrosion 9.625inch)
20.5 Parameter Listing
21. One Very Hi-Res Repeat 10in=100ft
21.1 Integration Summary
21.2 Software Version
21.3 Composite Summary
21.4 Log (LBV1_USI Corrosion 9.625inch)
21.5 Parameter Listing
22. One Very Hi-Res Repeat 10in=100ft
22.1 Integration Summary
22.2 Software Version
22.3 Composite Summary
22.4 Log (LBV1_USI Corrosion 9.625inch)
22.5 Parameter Listing
23. XYZ (USI Fluid Acoustic Slowness vs Depth)
24. XYZ (USI Theoretical Acoustic impedance of mud vs Depth)
25. Tail

Well Sketch





Borehole Size/Casing/Tubing Record

Bit						
Bit Size (in)	17.5	12.25	15			
Top Driller (ft)	0	814	6899			
Top Logger (ft)	0	814	6899			
Bottom Driller (ft)	814	6899	7170			
Bottom Logger (ft)	814	6899	7170			
Casing						
Size (in)	13.375	9.625	5.5			
Weight (lbm/ft)	54.5	47	17			
Inner Diameter (in)	12.615	8.681	4.892			
Grade	K55	N80	K55			
Top Driller (ft)	0	0	6816			
Top Logger (ft)	0	0	6816			
Bottom Driller (ft)	814	6899	7170			
Bottom Logger (ft)	814	6899	7170			

Remarks and Equipment Summary

One: Toolstring

Equip name	Length	MP name	Offset
LEH-QT:2 867	59.39	Red	
LEH-QT:28			

One: Remarks

13 3/8 casing cemented with 761 ft3 class G cement returns to surface

9 5/8 inch casing cemented with 2604 ft3 cement returns to surface

67

DTC-H 56.47
ECH-KC
DTC-H

HGNS-H:3923 53.47
HGNH:4819
NSR-F:5002
NPV-N
HACCZ-H:3923
HGNS-H:3923
HMCA-H

AH-184[4] 44.06

AH-184[3]:2985 42.06

DSLT-H:8236 40.06
ECH-KH:8678
DSLC-H:8236
SLS-E:1206

AH-184[2]:2882 19.42

AH-184[1]:6735 17.42

USIT-E:1764 15.42
ECH-MFA:1764
USAC-A:1

CTEM	**55.57**
HV	**0.00**
TelStatus	**53.47**
ToolStatus	**53.47**
Temperature	**53.44**
GR	**52.73**
CNL Porosity	**46.4**
HGNS	**44.06**
HMCA	**44.06**
Accelerometer	**0.00**
CBL 3ft	**27.59**
Upper-Near	**27.59**
VDL 5ft	**26.59**
Upper-Far	**26.59**
Delta-T	**25.22**
Lower-Far	**23.84**
Lower-Near	**22.84**
SLS-E	**19.42**

cement , returns to surface

second hi-res repeat run from 1690 ft to 840 ft with a frequency of 600 khz

Toolstring ran as per tool sketch

Two centralizers on USIS and two CME-Y used to centralize USIT tool

Rig: Ensign 321

Anomolies repeated in Hi-Res

No pressure applied during log

Crew: Allan,Coupart
Correlated to SLB Dual Laterolog dated 12-19

Bridge plug set at 6800 ft, tagged at 6796 ft

Logging Objective: Corrosion and cement

USIT Logged at 10 Deg 1.5 inch logging speed 2800 fph, hi-res 10 deg 0.6 inch speed 1000 fp

Logged form td 6796 ft to BOP at 23.5 ft
Thank you for choosing Schlumberger

764
USIS-A:27
20
USSC-B
USRS-C:84
0
USI-SENS
OR:3349



Lengths are in ft
Maximum Outer Diameter = 6.690 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO

Job Event Summary

Event	Time	Duration	Interval	Remark
Leave Base				
Arrival At Wellsite				
Safety Meeting				
Rig Up Surface Equipment				
Rig Down				
Leave Wellsite				
Return To Base				

USIT - Fluid Properties Measurement

Run Name	Pass Name	Start Depth(ft)	Stop Depth(ft)
Fluid Velocity			
Start Depth(ft)	**Stop Depth(ft)**	**Start Value(us/ft)**	**End Value(us/ft)**
Mud Impedance			
Start Depth(ft)	**Stop Depth(ft)**	**Start Value(Mrayl)**	**End Value(Mrayl)**

Composite 1

Main Pass 5 in = 100 ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Computation	Description	Version
CEVAL	Sonic Cement Evaluation Computation Ensemble provides common Parameters and Channels	6.1.58882.3100
Cementation	Cementation Computation Application	6.1.58882.3100

SoftwareVersion_Tool	SoftwareVersion_Run Version	SoftwareVersion_Build Version
WAFE-SEC	Synergy SV451EC version 9.10	Synergy SV451EC version 9.10
WAFE-FEC	Synergy SV451EC version 9.10	Synergy SV451EC version 9.10
WAFE-TMDI	Synergy SV451EC version 46.19	Synergy SV451EC version 46.19

Tool Elements	Description	Software Version	Firmware Version
HGNS-H	HILT Gamma-Ray and Neutron Sonde, 150 degC	6.1.58882.3100	2.0
SLS-E	Sonic Logging Sonde E supports 3'-5'BHC DT and CBL/VDL	6.1.58882.3100	4.0
USI-SENSOR	USIT Transducer Element	6.1.58882.3100	DSP: v1.82

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[2]:Up	Up	95.87 ft	6797.82 ft	18-May-2016 9:05:04 AM	18-May-2016 11:40:12 AM	ON	2.00 ft	No
One	Log[12]:Up	Up	21.60 ft	301.21 ft	18-May-2016 3:54:44 PM	18-May-2016 4:04:32 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

Composite 1:S002

Description: USI VDL Cement Format: Log (LBV1_USI-VDL (DSLT) Cement 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:10:05

TIME_1900 - Time Marked every 60.00 (s)




60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
BI
ERAV_RF
ERAV_RF
220
230
240
250
260
270


280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
ECGR
ECGR_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
FRAV_RF
FRAV_RF
AIMX
AIAV
AIMN
BI


ERAV_RF
ERAV_RF
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
ECGR
ECCE_RF
TRMX_RF
TRAV_RF
BI


IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIAV
AIMN
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140
1150


ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360
1370


1380
1390
1400
ECGR
ECOE_RF
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
1420
IRAV_RF
IRMN_RF
AIAV
1430
ERAV_RF
ERAV_RF
AIMN
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580
1590


1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
ECGR
ECGR_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIAV
AIMN
BI


1820
1830
1840
1850
1860
1870
1880
ECGR
ECOE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
1900
1910
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020
2030


2040
2050
2060
2070
2080
2090
2100
2110
2120
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
2140
2150
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI
2160
2170
2180
2190
2200
2210
2220
2230
2240
2250


2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
BI
2620
2630
ERAV_RF
ERAV_RF
AIMN
2640
2650
2660
2670
2680
2690


2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
ECGR
2850
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
BI
2860
2870
ERAV_RF
ERAV_RF
2880
2890
2900
2910


2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
ECGR
ECOE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
3100
3110
3120
3130
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
BI


3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3340
3350
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
AIMX
AIAV
AIMN
BI


ERAV_RF
ERAV_RF
RMIN
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560
ECGR
ECCE_RF
RMX_RF
RAV_RF
BI


IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780
3790


3800
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI
3820
IRMN_RF
IRMX_RF
AIMX
IRAV_RF
IRMN_RF
AIAV
3830
ERAV_RF
ERAV_RF
AIMN
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000
4010


4020
4030
4040
ECGR
ERMX_RF
4050
IRMX_RF
IRAV_RF
BI
4060
IRMN_RF
IRMX_RF
AIMX
4070
IRAV_RF
IRMN_RF
AIAV
ERAV_RF
ERAV_RF
AIMN
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220
4230


4240
4250
4260
4270
4280
ECGR
ECOE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
4300
4310
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
B
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440
4450


4460
4470
4480
4490
4500
4510
4520
ECGR
ECGE_RF
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
AIMX
4540
IRAV_RF
RMN_RF
AIAV
4550
ERAV_RF
ERAV_RF
AIMN
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660
4670


4680
4690
4700
4710
4720
4730
4740
4750
4760
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
4780
4790
ERAV_RF
ERAV_RF
AIAV
AIMN
BI
4800
4810
4820
4830
4840
4850
4860
4870
4880
4890


4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV_RF
AIMN
BI


5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
ECGR
5250
IRMX_RF
IRAV_RF
BI
IRMN_RF
IRMX_RF
5260
IRAV_RF
IRMN_RF
5270
ERAV_RF
ER
AMN
5280
5290
5300
5310
5320
5330


5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
5500
5510
ERAV_RF
ER
AHMN
BI
5520
5530
5540
5550


5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ERAV
AHMN
BI


5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5980
5990
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
BI
AIA
AIMN


6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200
ECGR
ECCE_RF
IRMX_RF
IRAV_RF
BI


IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ER
AIMN
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420
6430


ECGR
ECALI_RF
IRMX_RF
IRAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
IRMN_RF
ERAV_RF
ER
AIMN
BI
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640
6650



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]

0 in 0.5

Gamma Ray (ECGR) HGNS[1]

0 gAPI 150

ERAV_IRAV

IRAV_LHF1

LHF1_ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]

5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]

5 in 4

ERAV_RHF1

IRAV_ERAV

RHF1_IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]

4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]

4 in 5

Maximum of

Absent 1.000 2.500 4.000 5.500 7.000

Custom Normalization

USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Acoustic Impedance Minimum (AIMN) USIT-E[1]

-1 Mrayl 9

Acoustic Impedance Average (AIAV) USIT-E[1]

-1 Mrayl 9

Acoustic Impedance Maximum (AIMX) USIT-E[1]

-1 Mrayl 9

Absent 0.300 3.581 5.054 6.527 8.000

Custom Normalization

USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)

Bonded

Gas

Liquid

Micro-debonding

Bond Index (BI) DSLT-H[1]

1 0

Min Amplitude Max

Sonic VDL Curve DSLT-H[1]

200 us 1200

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]	Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4	4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]	**Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]**
5 in 4	4 in 5

TIME_1900 - Time Marked every 60.00 (s)

Description: USI VDL Cement Format: Log (LBV1_USI-VDL (DSLT) Cement 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:10:05

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AMSG	Auxiliary Minimum Sliding Gate	DSLT-H	140	us
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BERJ	Bad Echo Rejection	USIT-E	On	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BILI	Bond Index Level for Zone Isolation	DSLT-H	0.8	
BS	Bit Size	WLSESSION	Depth Zoned	in
CASING_PRATIO	Casing Poisson Ratio	USIT-E	Standard Poisson Ratio	
CBLG	CBL Gate Width	DSLT-H	100	us
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CBRA	CBL LQC Reference Amplitude in Free Pipe	DSLT-H	52	mV
CDEN	Cement Density	HGNS-H	2	g/cm3
CMCF	CBL Cement Type Compensation Factor	DSLT-H	1	
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
DETE	Delta-T Detection	DSLT-H	E1	
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FCF	CBL Fluid Compensation Factor	DSLT-H	0.91	
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
GOBO_CURR	Good Bond in Arbitrary Cement	DSLT-H	4.74	mV
GR_MULTIPLIER	Gamma Ray Multiplier	HGNS-H	1	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MAHTR	Manual High Threshold Reference for first arrival detection	DSLT-H	120	
MATT_CURR	Maximum Attenuation in Arbitrary Cement	DSLT-H	9.3	dB/ft
MCI	Minimum Cemented Interval for Isolation	DSLT-H	Depth Zoned	ft
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MNHTR	Minimum High Threshold Reference for first arrival detection	DSLT-H	100	
MSA	Minimum Sonic Amplitude	DSLT-H	2.61	mV

MSA	Minimum Sonic Amplitude	DSLT-H	2.61	mV
MSA_CURR	Minimum Sonic Amplitude in Arbitrary Cement	DSLT-H	2.61	mV
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
MUD_N_THE	Theoretical Mud Normalization Factor	USIT-E	1	
NMSG	Near Minimum Sliding Gate	DSLT-H	280	us
NMXG	Near Maximum Sliding Gate	DSLT-H	950	us
NUMP	Number of Detection Passes	DSLT-H	2	
OPLEV	USIT Remove Flagged Data Level	USIT-E	OPT2	
RCOD	Reference Calibrator Outer Diameter	USIT-E	7	in
RCSO	Reference Calibrator Standoff	USIT-E	1.378	in
RCTH	Reference Calibrator Thickness	USIT-E	0.295	in
SDNV	Number of Vertical Samples used for Micro-debonding Computation	USIT-E	5	
SDTHOR	Acoustic Impedance STD Horizontal Threshold for Micro-debonding	USIT-E	0.5	Mrayl
SDTVER	Acoustic Impedance STD Vertical Threshold for Micro-debonding	USIT-E	0.3	Mrayl
SFAF	Sonic Formation Attenuation Factor	DSLT-H	3.25	dB/ft
SGAD	Sliding Gate Status	DSLT-H	Off	
SGCL	Sliding Gate Closing Delta-T	DSLT-H	130	us/ft
SGCW	Sliding Gate Closing Width	DSLT-H	25	us
SGDT	Sliding Gate Delta-T	DSLT-H	57	us/ft
SGW	Sliding Gate Width	DSLT-H	110	us
SLEV	Signal Level for AGC	DSLT-H	5000	mV
SOCN	Standoff Distance	HGNS-H	0.125	in
SOCO	Standoff Correction Option	HGNS-H	No	
TCUB	T^3 Processing Level	USIT-E	Loop	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	Time Zoned	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	Time Zoned	%
HISC	Tool Position: Centered or Eccentered	HGNS-H	Eccentered	
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
THDP	Thickness Detection Policy	USIT-E	Fundamental	
VCAS	Ultrasonic Transversal Velocity in Casing	USIT-E	51.4	us/ft
VDLG	VDL Manual Gain	DSLT-H	5	
ZCAS	Acoustic Impedance of Casing	USIT-E	46.25	Mrayl
ZCMT	Acoustic Impedance of Cement	DSLT-H	6.8	Mrayl
ZCMT_NEAT	Acoustic Impedance of Cement in Neat Cement	DSLT-H	6.8	Mrayl
ZINI	Initial Estimate of Cement Impedance	USIT-E	-1	Mrayl
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

OneDepth Zoned Parameters

Parameter	Value	Start (ft)	Stop (ft)
BS	17.5	10	814
BS	12.25	814	6797.5
MCI	21.68	10	814
MCI	14.21	814	6797.5

MCI	14.81	814	6797.5

All depth are actual.

OneTime Zoned Parameters

Pass Log[2]:Up

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
THDH	115	18-May-2016 09:05:20	18-May-2016 11:40:12	6797.82	95.87
THDL	60	18-May-2016 09:05:20	18-May-2016 11:40:12	6797.82	95.87

Pass Log[12]:Up

THDH	130	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64
THDL	70	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64

All depth are at tool zero.

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
DDEL	Digitizing Delay	DSLT-H	0	us
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
DOT(DOS)	Distance between Opposite Transducer Faces	USIT-E	4.874	in
MODE	DSLT Acquisition Mode	DSLT-H	CBLB	
RATE	DSLT Firing Rate	DSLT-H	15 Hz	
DTFS	DSLT Telemetry Frame Size	DSLT-H	536	
DWCO	Digitizer Word Count	DSLT-H	250	
EMXV	EMEX Voltage	USIT-E	Time Zoned	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
SDTH	Switch Down Threshold	DSLT-H	20000	
SGAI	Selectable Acquisition Gain	DSLT-H	x1	
SUTH	Switch Up Threshold	DSLT-H	1000	
TMUC	Type of Mud	USIT-E	BRI	
UACLV_PERM	Ultrasonic ACLV Permanent	USIT-E	No	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 1.5 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
USSP	Ultrasonic Service	USIT-E	USI	
VRES	Vertical Resolution	USIT-E	1.5 in	
WINB	Window Begin Time	USIT-E	Time Zoned	us
WINE	Window End Time	USIT-E	Time Zoned	us
WMOD	Waveform Firing Mode	DSLT-H	Full	

OneTime Zoned Parameters

Pass Log[2]:Up

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
EMXV	45	18-May-2016 09:05:20	18-May-2016 11:40:12	6797.82	95.87
WINB	45.35	18-May-2016 09:05:04	18-May-2016 09:27:18	6797.82	5941.2

WINB	41.8	18-May-2016 09:27:18	18-May-2016 11:40:12	5941.2	95.87
WINE	85.35	18-May-2016 09:05:04	18-May-2016 09:27:20	6797.82	5939.37
WINE	87.99	18-May-2016 09:27:20	18-May-2016 11:40:12	5939.37	95.87

Pass Log[12]:Up

EMXV	32	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64
WINB	45.35	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64
WINE	85.35	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64

All depth are at tool zero.

Composite 1

Main Pass 5 IN = 100 FT

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[2]:Up	Up	95.87 ft	6797.82 ft	18-May-2016 9:05:04 AM	18-May-2016 11:40:12 AM	ON	2.00 ft	No
One	Log[12]:Up	Up	21.60 ft	301.21 ft	18-May-2016 3:54:44 PM	18-May-2016 4:04:32 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

Composite 1:S002

Description: USI Composite Format: Log (LBV1_USI Composite 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth

Creation Date: 18-May-2016 19:10:41

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :

2 - UFLG 2 Value within [1.5 - 2.5] - :

3 - UFLG 3 Value within [2.5 - 3.5] - :

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error

Pulse Origin Not Detected

WINLEN Error

Casing Thickness Error

Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)




Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5
Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]
USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5
Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]
0 dB 75
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1]
(in)
Maximum of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E[1]
0.1 in 0.6
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1]
(in)
Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1]
(Mrayl)
Bonded
Gas
Liquid
Micro-debonding
Bond Index (BI) DSLT-H[1]
1 0
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1]
(Mrayl)
Splice
10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170


Splice
Splice
Splice
Splice
Splice
Splice
Splice
Splice
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390


400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610


620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830


840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


1060
1070
1080
1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270


1280
1290
1300
1310
1320
1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490


1500
1510
1520
1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710


1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


1940
1950
1960
1970
1980
1990
2000
2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150


2160
2170
2180
2190
2200
2210
2220
2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370


2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590


2600
2610
2620
2630
2640
2650
2660
2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810


2820
2830
2840
2850
2860
2870
2880
2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


3040
3050
3060
3070
3080
3090
3100
3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250


3260
3270
3280
3290
3300
3310
3320
3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470


3480
3490
3500
3510
3520
3530
3540
3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690


3700
3710
3720
3730
3740
3750
3760
3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
RSAV
ECCE_RF
IRMN_RF
IRMN_RF
AWMX_RF
IRMX_RF
IRMX_RF
AWAV_RF
IRAV_RF
IRAV_RF
AWMN_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


3920
3930
3940
3950
3960
3970
3980
3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130


4140
4150
4160
4170
4180
4190
4200
4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350


4360
4370
4380
4390
4400
4410
4420
4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570


4580
4590
4600
4610
4620
4630
4640
4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


4800
4810
4820
4830
4840
4850
4860
4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010


5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230


5240
5250
5260
5270
5280
5290
5300
5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450


5460
5470
5480
5490
5500
5510
5520
5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670


5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI


5900
5910
5920
5930
5940
5950
5960
5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110


6120
6130
6140
6150
6160
6170
6180
6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330


6340
6350
6360
6370
6380
6390
6400
6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550


6560
6570
6580
6590
6600
6610
6620
6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
BI



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]

USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5

Absent -4.799 -2.799 -0.800
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1] (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]
0 dB 75

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5

Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1] (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E[1]
0.1 in 0.6

Absent -0.051 -0.012 0.028 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1] (in)

Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Ratio of Cement Measurements to Total (CEMR) USIT-E[1]
1 0

Micro-debonding Ratio (MDR) USIT-E[1]
1 0

Ratio of Gas Measurements to Total (GASR) USIT-E[1]
1 0

Bonded
Gas
Liquid
Micro-debonding

Bond Index (BI) DSLT-H[1]
1 0

Absent 3.090 5.054 7.018
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)

Absent 2.599 4.563 6.527
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

Description: USI Composite Format: Log (LBV1_USI Composite 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:10:41

Composite 1

Cement Log 2 IN = 100 FT

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data

									Parallel Data
One	Log[2]:Up	Up	95.87 ft	6797.82 ft	18-May-2016 9:05:04 AM	18-May-2016 11:40:12 AM	ON	2.00 ft	No
One	Log[12]:Up	Up	21.60 ft	301.21 ft	18-May-2016 3:54:44 PM	18-May-2016 4:04:32 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

Composite 1:S002

Description: USI Cement Format: Log (LBV1_USI Cement 9.625inch) Index Scale: 2 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:11:31

TIME_1900 - Time Marked every 60.00 (s)




Splice
Splice
Splice
Splice
Splice
Splice
200
250
300
350
400
450
500
550
600
650
700


750
800
850
900
950
1000
1050
1100
1150
1200
1250
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN


1300
1350
1400
1450
1500
1550
1600
1650
1700
1750
1800


1850
1900
1950
2000
2050
2100
2150
2200
2250
2300
2350
ECGE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
AIMX


IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
AIAV
AIMN
2400
2450
2500
2550
2600
2650
2700
2750
2800
2850
2900


2950
3000
3050
3100
3150
3200
3250
3300
3350
3400
3450


ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
AIMX
AIAV
AIMN
3500
3550
3600
3650
3700
3750
3800
3850
3900
3950
4000


4050
4100
4150
4200
4250
4300
4350
4400
4450
4500
4550


4600
4650
4700
4750
4800
4850
4900
4950
5000
5050
5100
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
IMX
AIAV
AIMN


5150
5200
5250
5300
5350
5400
5450
5500
5550
5600
5650


5700
5750
5800
5850
5900
5950
6000
6050
6100
6150
6200
ECCE_RF
ECGR
IRMX_RF
IRMX_RF
IRMN_RF
IRMN_RF
IRAV_RF
IRAV_RF
ERAV_RF
AIAV
AIMN


6250
6300
6350
6400
6450
6500
6550
6600
6650
6700
6750



TIME_1900 - Time Marked every 60.00 (s)

Description: USI Cement Format: Log (LBV1_USI Cement 9.625inch) Index Scale: 2 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:11:32

Composite 1

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[2]:Up	Up	95.87 ft	6797.82 ft	18-May-2016 9:05:04 AM	18-May-2016 11:40:12 AM	ON	2.00 ft	No
One	Log[12]:Up	Up	21.60 ft	301.21 ft	18-May-2016 3:54:44 PM	18-May-2016 4:04:32 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:12:07

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Gamma Ray (EHGR) HGNS[1]
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]

USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1] (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1] (in)

Internal Radius Averaged Value (IRAV) USIT-E[1]
4 in 5

Internal Radius Maximum Value (IRMX) USIT-E[1]
4 in 5

Internal Radius Minimum Value (IRMN) USIT-E[1]
4 in 5

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E[1]
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1] (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E[1]
0.1 in 0.6




70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
THGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
EHGR
RSAV
AWMX_RF
IRMN
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
THMX_RF
THAV_RF


ECCE_RF
AWAV_RF
AWMN_RF
IRMX
IRAV
IRAV_RF
ERAV_RF
IRAV_RF
ERAV_RF
THNO
THMN_RF
EHGR
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140
1150
1160


RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360
1370
1380


1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580
1590
1600
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1610
1620
1630
1640
EHGR
1650
RSAV
1660
ECCE_RF
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
1820
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1830
1840
1850
1860
1870
1880
EHGR
1890
RSAV
1900
ECCE_RF
1910
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020
2030
2040
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


2050
2060
2070
2080
2090
2100
2110
2120
EHGR
2130
RSAV
2140
ECCE_RF
2150
2160
2170
2180
2190
2200
2210
2220
2230
2240
2250
2260
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
2480
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


2400
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
EHGR
2610
RSAV
2620
ECCE_RF
2630
2640
2650
2660
2670
2680
2690
2700
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
2890
2900
2910
2920
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100
3110
3120
3130
3140
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3330
3340
3350
3360
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560
3570
3580
EHGR
RSAV
AWMX_RF
IRMN
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
THMX_RF
THAV_RF


ECCE_RF
AWAV_RF
AWMN_RF
IRMX
IRAV
IRAV_RF
ERAV_RF
IRAV_RF
ERAV_RF
THNO
THMN_RF
EHGR
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780
3790
3800


RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000
4010
4020


4030
4040
EHGR
4050
RSAV
4060
ECCE_RF
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220
4230
4240
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


4250
4260
4270
4280
EHGR
4290
RSAV
4300
ECCE_RF
4310
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440
4450
4460
AWMX_RF
AWAV_RF
AWMN_RF
RMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


4470
4480
4490
4500
4510
4520
EHGR
4530
RSAV
4540
ECCE_RF
4550
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660
4670
4680
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
4870
4880
4890
4900
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
5120
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
EHGR
5250
RSAV
5260
ECCE_RF
5270
5280
5290
5300
5310
5320
5330
5340
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
5490
5500
5510
5520
5530
5540
5550
5560
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
5780
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5970
5980
5990
6000
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200
6210
6220
EHGR
RSAV
AWMX_RF
IRMN
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
THMX_RF
THAV_RF


ECCE_RF
AWAV_RF
AWMN_RF
IRMX
IRAV
IRAV_RF
ERAV_RF
IRAV_RF
ERAV_RF
THNO
THMN_RF
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420
6430
6440
EHGR


6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640
6650
6660
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN
IRMX
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E[1]
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8

Gamma Ray (EHGR) HGNS[1]
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E[1]

USIT Processing Flags (UFLG[0]) USIT-E[1]
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E[1] (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E[1]
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E[1]
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E[1] (in)

Internal Radius Averaged Value (IRAV) USIT-E[1]
4 in 5

Internal Radius Maximum Value (IRMX) USIT-E[1]
4 in 5

Internal Radius Minimum Value (IRMN) USIT-E[1]
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
5 in 4

Maximum of Unflagged Internal Radii

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E[1]
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E[1]
4 in 5

Maximum of Unflagged Internal Radii

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E[1] (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E[1]
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E[1]
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E[1]
0.1 in 0.6

Maximum of Unflagged Casing Thickness

0 dB 75	(IRMX_RF) USIT-E[1]	(IRMX_RF) USIT-E[1]		Thickness (THMX_RF) USIT-E[1]
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E[1]	5 in 4	4 in 5		0.1 in 0.6
0 dB 75	Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]	Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E[1]		
	5 in 4	4 in 5		

USIT Processing Flags (UFLG[0]) USIT-E[1]

1 - UFLG 1 Value within [0.0 - 1.5] - :	UTIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:12:07

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	Depth Zoned	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	Time Zoned	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	Time Zoned	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	

ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

OneDepth Zoned Parameters

Parameter	Value	Start (ft)	Stop (ft)
BS	17.5	15	814
BS	12.25	814	6797.5

All depth are actual.

OneTime Zoned Parameters

Pass Log[2]:Up

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
THDH	115	18-May-2016 09:05:20	18-May-2016 11:40:12	6797.82	95.87
THDL	60	18-May-2016 09:05:20	18-May-2016 11:40:12	6797.82	95.87

Pass Log[12]:Up

THDH	130	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64
THDL	70	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64

All depth are at tool zero.

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	Time Zoned	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 1.5 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	1.5 in	
WINB	Window Begin Time	USIT-E	Time Zoned	us
WINE	Window End Time	USIT-E	Time Zoned	us

OneTime Zoned Parameters

Pass Log[2]:Up

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
EMXV	45	18-May-2016 09:05:20	18-May-2016 11:40:12	6797.82	95.87
WINB	45.35	18-May-2016 09:05:04	18-May-2016 09:27:18	6797.82	5941.2
WINB	41.8	18-May-2016 09:27:18	18-May-2016 11:40:12	5941.2	95.87
WINE	85.35	18-May-2016 09:05:04	18-May-2016 09:27:20	6797.82	5939.37
WINE	87.99	18-May-2016 09:27:20	18-May-2016 11:40:12	5939.37	95.87

Pass Log[12]:Up

EMXV	32	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64
WINB	45.35	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64
WINE	85.35	18-May-2016 15:58:15	18-May-2016 16:04:32	190.26	21.64

All depth are at tool zero.

Composite 1

USI Compressed Goodwin

Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[2]:Up	Up	95.87 ft	6797.82 ft	18-May-2016 9:05:04 AM	18-May-2016 11:40:12 AM	ON	2.00 ft	No
One	Log[12]:Up	Up	21.60 ft	301.21 ft	18-May-2016 3:54:44 PM	18-May-2016 4:04:32 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

Composite 1:S002

Description: USI Goodwin Format: Log (Import of USI Goodwin) Index Scale: 0.1 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:12:49

TIME_1900 - Time Marked every 60.00 (s)

Minimum Acoustic Impedance 1 (MIN_AI1) USIT-E[1]	Minimum Acoustic Impedance 3 (MIN_AI3) USIT-E[1]	Minimum Acoustic Impedance 5 (MIN_AI5) USIT-E[1]	Minimum Acoustic Impedance 7 (MIN_AI7) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10
Maximum Acoustic Impedance 1 (MAX_AI1) USIT-E[1]	Maximum Acoustic Impedance 3 (MAX_AI3) USIT-E[1]	Maximum Acoustic Impedance 5 (MAX_AI5) USIT-E[1]	Maximum Acoustic Impedance 7 (MAX_AI7) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10
Average Acoustic Impedance 1 (AV_AI1) USIT-E[1]	Average Acoustic Impedance 3 (AV_AI3) USIT-E[1]	Average Acoustic Impedance 5 (AV_AI5) USIT-E[1]	Average Acoustic Impedance 7 (AV_AI7) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10

Minimum Acoustic Impedance 2 (MIN_AI2) USIT-E[1]	Minimum Acoustic Impedance 4 (MIN_AI4) USIT-E[1]	Minimum Acoustic Impedance 6 (MIN_AI6) USIT-E[1]	Minimum Acoustic Impedance 8 (MIN_AI8) USIT-E[1]	Minimum Acoustic Impedance 9 (MIN_AI9) USIT-E[1]	Acoustic Impedance Minimum (AIMN) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	-1 Mrayl 9
Maximum Acoustic Impedance 2 (MAX_AI2) USIT-E[1]	Maximum Acoustic Impedance 4 (MAX_AI4) USIT-E[1]	Maximum Acoustic Impedance 6 (MAX_AI6) USIT-E[1]	Maximum Acoustic Impedance 8 (MAX_AI8) USIT-E[1]	Maximum Acoustic Impedance 9 (MAX_AI9) USIT-E[1]	Acoustic Impedance Maximum (AIMX) USIT-E[1]
0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	-1 Mrayl 9
Average Acoustic Impedance 2	Average Acoustic Impedance 4	Average Acoustic Impedance 6	Average Acoustic Impedance 8	Average Acoustic Impedance 9	Acoustic Impedance Average

GR

0 gAPI 150

Motor Revolution Speed (RSAV) USIT-E[1]

6 c/s 8

Amplitude of

Absent 1.500 3.500 5.500 7.500

Custom Normalization

USIT - Acoustic

Bonded

Micro-Debonding

-1000.000 3.090 5.054 7.018

Custom Normalization

USIT - Acoustic Impedance With Micro-debonding Image


Eccentering (ECCE) USIT-E[1]
0 in 0.5
Impedance 2 (AV_AI2) USIT-E[1]
0 Mrayl 10
Impedance 4 (AV_AI4) USIT-E[1]
0 Mrayl 10
Impedance 6 (AV_AI6) USIT-E[1]
0 Mrayl 10
Impedance 8 (AV_AI8) USIT-E[1]
0 Mrayl 10
Impedance 9 (AV_AI9) USIT-E[1]
0 Mrayl 10
Average (AIAV) USIT-E[1]
-1 Mrayl 9
Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)
Liquid
Gas
ing Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)
0
500
1000
1500
2000
2500
3000
3500
4000
4500
5000
5500
6000
6500
GR
0 gAPI 150
Motor Revolution Speed (RSAV) USIT-E[1]
6 c/s 8
Amplitude of Eccentering (ECCE) USIT-E[1]
0 in 0.5
Minimum Acoustic Impedance 1 (MIN_AI1) USIT-E[1]
0 Mrayl 10
Minimum Acoustic Impedance 3 (MIN_AI3) USIT-E[1]
0 Mrayl 10
Minimum Acoustic Impedance 5 (MIN_AI5) USIT-E[1]
0 Mrayl 10
Minimum Acoustic Impedance 7 (MIN_AI7) USIT-E[1]
0 Mrayl 10
Minimum Acoustic Impedance 9 (MIN_AI9) USIT-E[1]
0 Mrayl 10
Acoustic Impedance Minimum (AIMN) USIT-E[1]
-1 Mrayl 9
Maximum Acoustic Impedance 1 (MAX_AI1) USIT-E[1]
0 Mrayl 10
Maximum Acoustic Impedance 3 (MAX_AI3) USIT-E[1]
0 Mrayl 10
Maximum Acoustic Impedance 5 (MAX_AI5) USIT-E[1]
0 Mrayl 10
Maximum Acoustic Impedance 7 (MAX_AI7) USIT-E[1]
0 Mrayl 10
Maximum Acoustic Impedance 9 (MAX_AI9) USIT-E[1]
0 Mrayl 10
Acoustic Impedance Maximum (AIMX) USIT-E[1]
-1 Mrayl 9
Average Acoustic Impedance 1 (AV_AI1) USIT-E[1]
Average Acoustic Impedance 3 (AV_AI3) USIT-E[1]
Average Acoustic Impedance 5 (AV_AI5) USIT-E[1]
Average Acoustic Impedance 7 (AV_AI7) USIT-E[1]
Average Acoustic Impedance 9 (AV_AI9) USIT-E[1]
Acoustic Impedance Average (AIAV) USIT-E[1]
Absent 1.500 3.500 5.500 7.500
Custom Normalization
USIT - Acoustic Impedance (AIBK) USIT-E[1] (Mrayl)
Bonded
Micro-Debonding
Liquid
Gas
-1000.000 3.090 5.054 7.018
Custom Normalization
USIT - Acoustic Impedance With Micro-debonding Image (AI_MDEBOND_IMG) USIT-E[1] (Mrayl)

0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	0 Mrayl 10	-1 Mrayl 9
Minimum Acoustic Impedance 2 (MIN_AI2) USIT-E[1] 0 Mrayl 10	Minimum Acoustic Impedance 4 (MIN_AI4) USIT-E[1] 0 Mrayl 10	Minimum Acoustic Impedance 6 (MIN_AI6) USIT-E[1] 0 Mrayl 10	Minimum Acoustic Impedance 8 (MIN_AI8) USIT-E[1] 0 Mrayl 10		
Maximum Acoustic Impedance 2 (MAX_AI2) USIT-E[1] 0 Mrayl 10	Maximum Acoustic Impedance 4 (MAX_AI4) USIT-E[1] 0 Mrayl 10	Maximum Acoustic Impedance 6 (MAX_AI6) USIT-E[1] 0 Mrayl 10	Maximum Acoustic Impedance 8 (MAX_AI8) USIT-E[1] 0 Mrayl 10		
Average Acoustic Impedance 2 (AV_AI2) USIT-E[1] 0 Mrayl 10	Average Acoustic Impedance 4 (AV_AI4) USIT-E[1] 0 Mrayl 10	Average Acoustic Impedance 6 (AV_AI6) USIT-E[1] 0 Mrayl 10	Average Acoustic Impedance 8 (AV_AI8) USIT-E[1] 0 Mrayl 10		

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Goodwin Format: Log (Import of USI Goodwin) Index Scale: 0.1 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:12:49

One

Very Hi-Res Repeat 10in=100ft at 600 khz

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[11]:Up	Up	840.64 ft	1692.26 ft	18-May-2016 3:01:48 PM	18-May-2016 3:50:08 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[11]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 18-May-2016 19:12:55

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - : Pulse Origin Not Detected

3 - UFLG 3 Value within [2.5 - 3.5] - : WINLEN Error

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - : Casing Thickness Error

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - : Loop Processing Error



Explicit Normalization

USIT - Amplitude of



Median of Unflagged External Radii (ERAV_RF) USIT-E

Median of Unflagged External Radii (ERAV_RF) USIT-E

Minimum of Unflagged Casing

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6




910
920
930
940
950
960
970
980
990
1000
1010
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
EHGR
BSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
THMX_RF
THAV_RF
THNO



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error
Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:12:55

One

Very Hi-Res Repeat 10in=100ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[10]:Up	Up	845.13 ft	1764.01 ft	18-May-2016 1:56:38 PM	18-May-2016 2:56:35 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[10]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:08

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV | ERAV-IRAV | IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV | ERAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6




860
870
880
890
900
910
920
930
940
950
960
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
THMX_RF
THAV_RF
THNO


AWMN_RF
ERAV_RF
ERAV_RF
THMN_RF
1080
1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
IRMX_RF
IRMN_RF
IRAV
EHGR


RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290


1300
EHGR
RSAV
ECCE_RF
1310
AWMX_RF
AWAV_RF
AWMN_RF
1320
1330
1340
1350
1360
1370
1380
1390
1400
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1520
1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
IRMN_RF
IRMX_RF
IRAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:08

One

Very Hi-Res Repeat 10in=100ft

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[9]:Up	Up	2245.51 ft	2358.50 ft	18-May-2016 1:47:14 PM	18-May-2016 1:54:26 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A
One: Log[9]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:22

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6


2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:22

One

Very Hi-Res Repeat 10in=100ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include

									Parallel Data
One	Log[8]:Up	Up	2959.70 ft	3110.39 ft	18-May-2016 1:34:25 PM	18-May-2016 1:44:10 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[8]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:29

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)




2980
EHGR
RSAV
ECCE_RF
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV | IRAV
ERAV-IRAV | ERAV
IRAV | IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4 | 4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4 | 4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4 | 4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4 | 4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:29

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	12.25	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	115	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	60	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	32	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	

UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 0.6 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	0.6 in	
WINB	Window Begin Time	USIT-E	45.35	us
WINE	Window End Time	USIT-E	85.35	us

One

Very Hi-Res Repeat 10in=100ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[7]:Up	Up	3380.69 ft	3561.66 ft	18-May-2016 1:22:22 PM	18-May-2016 1:32:22 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[7]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:37

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error




Speed (RSAV) USIT-E
6 c/s 8
Gamma Ray (EHGR) HGNS-H
0 gAPI 150
Processing Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5
0 dB 75
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75
Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E
(in)
0.1 in 0.6
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
EHGR
RSAV
AWMX_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
THMX_RF
THAV_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E

0 in 0.5

Motor Revolution Speed (RSAV) USIT-E

Absent 1.500 3.500

Explicit Normalization

USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0])

Absent -5.200 -3.600 -2.000 -0.400

Explicit Normalization

USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Absent -0.059 -0.028 0.004 0.035 0.068

Explicit Normalization

USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E

Internal Radius Averaged Value (IRAV) USIT-E

4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E

4 in 5

ERAV

ERAV-IRAV

IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E

IRAV

ERAV

IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E

Absent -0.059 -0.028 0.004 0.035 0.068

Explicit Normalization

USIT - Unflagged Casing Thickness minus Median of Unflagged Casing

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E

0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E

0.1 in 0.6



USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:37

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	12.25	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us

MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	115	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	60	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	32	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 0.6 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	0.6 in	
WINB	Window Begin Time	USIT-E	45.35	us
WINE	Window End Time	USIT-E	85.35	us

One

Very Hi-Res Repeat 10in=100ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[6]:Up	Up	4256.17 ft	4368.72 ft	18-May-2016 1:11:27 PM	18-May-2016 1:18:11 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[6]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:45

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :
2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

UTIM Error
Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6





Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E
(dB)

Minimum of Unflagged Wave Amplitude

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E
(in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged



Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	12.25	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	115	%

THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	60	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	32	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 0.6 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	0.6 in	
WINB	Window Begin Time	USIT-E	45.35	us
WINE	Window End Time	USIT-E	85.35	us

One

Very Hi-Res Repeat 10in=100ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[5]:Up	Up	4965.56 ft	5072.64 ft	18-May-2016 1:01:45 PM	18-May-2016 1:08:24 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[5]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:52

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - :
3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

Pulse Origin Not Detected
WINLEN Error
Casing Thickness Error
Loop Processing Error

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6





Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of

(AWAV_RF) USIT-E		
0	dB	75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E		
0	dB	75

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E		
5	in	4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E		
4	in	5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E		
5	in	4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E		
4	in	5

Unflagged Casing Thickness (THMX_RF) USIT-E		
0.1	in	0.6

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - : Pulse Origin Not Detected

3 - UFLG 3 Value within [2.5 - 3.5] - : WINLEN Error

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - : Casing Thickness Error

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - : Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:13:52

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	12.25	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	115	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	60	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	

USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	32	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 0.6 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	0.6 in	
WINB	Window Begin Time	USIT-E	45.35	us
WINE	Window End Time	USIT-E	85.35	us

One

Very Hi-Res Repeat 10in=100ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[4]:Up	Up	5808.07 ft	6254.64 ft	18-May-2016 12:31:51 PM	18-May-2016 12:58:04 PM	ON	0.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[4]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:14:00

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - : Pulse Origin Not Detected

3 - UFLG 3 Value within [2.5 - 3.5] - : WINLEN Error

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - : Casing Thickness Error

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - : Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

ERAV IRAV


Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5
Motor Revolution Speed (RSAV) USIT-E
6 c/s 8
Gamma Ray (EHGR) HGNS-H
0 gAPI 150
Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E
USIT Processing Flags (UFLG[0]) USIT-E
1 5
Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)
Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75
Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75
Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)
Internal Radius Averaged Value (IRAV) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
ERAV-IRAV
IRAV
Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4
ERAV
IRAV-ERAV
Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5
Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5
Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5
Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5
Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)
Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6
Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6
Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6
Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6
5810
5820
5830
5840
5850
IRMX_RF
IRMN_RF
IRAV


5860
EHGR
RSAV
ECCE_RF
5870
AWMX_RF
AWAV_RF
AWMN_RF
5880
5890
5900
5910
5920
5930
5940
5950
5960
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF
IRMX_RF


5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing

USIT-E

0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E

0 dB 75

Unflagged Internal Radii (IRMX_RF) USIT-E

5 in 4

Unflagged Internal Radii (IRMX_RF) USIT-E

4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E

5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E

4 in 5

Casing Thickness (THMX_RF) USIT-E

0.1 in 0.6

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - :

2 - UFLG 2 Value within [1.5 - 2.5] - :

3 - UFLG 3 Value within [2.5 - 3.5] - :

4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :

5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

- UTIM Error
- Pulse Origin Not Detected
- WINLEN Error
- Casing Thickness Error
- Loop Processing Error

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:14:00

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	12.25	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	115	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	60	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	

USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	Time Zoned	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 0.6 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	0.6 in	
WINB	Window Begin Time	USIT-E	45.35	us
WINE	Window End Time	USIT-E	85.35	us

Time Zone Parameters

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
EMXV	35	18-May-2016 12:31:51	18-May-2016 12:33:11	6254.64	6231.38
EMXV	32	18-May-2016 12:33:11	18-May-2016 12:58:04	6231.38	5808.07

All depth are at tool zero.

One

Very Hi-Res Repeat 10in=100ft

Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
One	Log[3]:Up	Up	6490.69 ft	6790.63 ft	18-May-2016 12:11:11 PM	18-May-2016 12:30:13 PM	ON	10.00 ft	No

All depths are referenced to toolstring zero

Log

Company:Southern California Gas Company Well:PORTER 72A

One: Log[3]:Up:S002

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:14:12

TIME_1900 - Time Marked every 60.00 (s)

USIT Processing Flags (UFLG[0]) USIT-E

1 - UFLG 1 Value within [0.0 - 1.5] - : UTIM Error

2 - UFLG 2 Value within [1.5 - 2.5] - : Pulse Origin Not Detected

3 - UFLG 3 Value within [2.5 - 3.5] - :
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :

WINLEN Error
Casing Thickness Error
Loop Processing Error

Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6




6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF


6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
EHGR
RSAV
ECCE_RF
AWMX_RF
AWAV_RF
AWMN_RF
IRMX_RF
IRMN_RF
IRAV
IRMN_RF
IRMN_RF
IRMX_RF
IRMX_RF
IRAV_RF
IRAV_RF
ERAV_RF
ERAV_RF
THMX_RF
THAV_RF
THNO
THMN_RF



Amplitude of Eccentering for Unflagged Waves (ECCE_RF) USIT-E
0 in 0.5

Motor Revolution Speed (RSAV) USIT-E
6 c/s 8

Gamma Ray (EHGR) HGNS-H
0 gAPI 150

Absent 1.500 3.500
Explicit Normalization
USIT - USIT Processing Flags (UFLG) USIT-E

USIT Processing Flags (UFLG[0]) USIT-E
1 5

Absent -5.200 -3.600 -2.000 -0.400
Explicit Normalization
USIT - Amplitude of Unflagged Wave (AWBK_RF) USIT-E (dB)

Minimum of Unflagged Wave Amplitude (AWMN_RF) USIT-E
0 dB 75

Average of Unflagged Wave Amplitude (AWAV_RF) USIT-E
0 dB 75

Maximum of Unflagged Wave Amplitude (AWMX_RF) USIT-E
0 dB 75

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Internal Radii minus Median Internal Radius (IRBKM_RF) USIT-E (in)

Internal Radius Averaged Value (IRAV) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

ERAV
ERAV-IRAV
IRAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
5 in 4

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
5 in 4

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
5 in 4

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
5 in 4

IRAV
ERAV
IRAV-ERAV

Median of Unflagged External Radii (ERAV_RF) USIT-E
4 in 5

Median Internal Radius of Casing Corrected for Eccentering (IRAV_RF) USIT-E
4 in 5

Maximum of Unflagged Internal Radii (IRMX_RF) USIT-E
4 in 5

Minimum of Unflagged Internal Radii (IRMN_RF) USIT-E
4 in 5

Absent -0.059 -0.028 0.004 0.035 0.068
Explicit Normalization
USIT - Unflagged Casing Thickness minus Median of Unflagged Casing Thickness (THBKM_RF) USIT-E (in)

Minimum of Unflagged Casing Thickness (THMN_RF) USIT-E
0.1 in 0.6

Nominal Casing Thickness (THNO) USIT-E
0.1 in 0.6

Median of Unflagged Casing Thickness (THAV_RF) USIT-E
0.1 in 0.6

Maximum of Unflagged Casing Thickness (THMX_RF) USIT-E
0.1 in 0.6

USIT Processing Flags (UFLG[0]) USIT-E
1 - UFLG 1 Value within [0.0 - 1.5] - ;

UTIM Error

1 - UFLG 1 Value within [0.0 - 1.5] - :	STIM Error
2 - UFLG 2 Value within [1.5 - 2.5] - :	Pulse Origin Not Detected
3 - UFLG 3 Value within [2.5 - 3.5] - :	WINLEN Error
4 - UFLG 4 UFLG 5 UFLG 6 Value within [3.5 - 6.5] - :	Casing Thickness Error
5 - UFLG 7 UFLG 8 UFLG 9 Value within [6.5 - 10] - :	Loop Processing Error

TIME_1900 - Time Marked every 60.00 (s)

Description: USI Composite Format: Log (LBV1_USI Corrosion 9.625inch) Index Scale: 10 in per 100 ft Index Unit: ft Index Type: Measured Depth
Creation Date: 18-May-2016 19:14:12

Channel Processing Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Cased	
BS	Bit Size	WLSESSION	12.25	in
CBLO	Casing Bottom (Logger)	WLSESSION	7170	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CMTY(U-USIT_CEMT)	Cement Type	USIT-E	Regular Cement	
THNO	Nominal Casing Thickness - Zoned along logger depths	WLSESSION	0.472	in
CYSTLGR	Casing Yield Strength - Zoned along logger depths	WLSESSION	80000	psi
DFD	Drilling Fluid Density	Borehole	9.3	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DTMD	Borehole Fluid Slowness	Borehole	206	us/ft
FDII	FPM Data Interpolation Interval	USIT-E	0	ft
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	BS	
HEMA	Hematite Presence Flag	Borehole	No	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	29.67	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	115	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	60	%
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	0.1	Mrayl
UFGDE	Fiberglass Density	USIT-E	1.95	g/cm3
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
USI_FSOD	USIT USI Fluid Slowness Fits Casing Outer Diameter	USIT-E	0_OFF	
USI_FVEL_SEL	USI Fluid Velocity Selection	USIT-E	Automatic	
USI_ZMUD_SEL	USI Mud Impedance Selection	USIT-E	FreePipe Norm.	
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Tool Control Parameters

One: Parameters

Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
EMXV	EMEX Voltage	USIT-E	Time Zoned	V

HRES	Horizontal Resolution	USIT-E	10 deg	
MOTOR_PROTECT	Motor Protection	USIT-E	Off	
TMUC	Type of Mud	USIT-E	BRI	
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 500 KHz	
UWKM	USIT Working Mode	USIT-E	Uncompressed 10 deg at 0.6 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6800	ft
VRES	Vertical Resolution	USIT-E	0.6 in	
WINB	Window Begin Time	USIT-E	45.35	us
WINE	Window End Time	USIT-E	85.35	us

Time Zone Parameters

Parameter	Value	Start Time	Stop Time	Start Depth (ft)	Stop Depth (ft)
EMXV	45	18-May-2016 12:11:11	18-May-2016 12:24:05	6790.63	6590.36
EMXV	40	18-May-2016 12:24:05	18-May-2016 12:25:05	6590.36	6574.14
EMXV	35	18-May-2016 12:25:05	18-May-2016 12:30:13	6574.14	6490.69

All depth are at tool zero.

XYZ

Company:Southern California Gas Company Well:PORTER 72A
One: Log[1]:Down:S002

Fluid Acoustic Slowness vs Depth

2D Cross Plot

Index Range: From 178.50 to 6803.00 ft





XYZ

Company:Southern California Gas Company Well:PORTER 72A
One: Log[1]:Down:S002

Theoretical Acoustic Impedance of Mud vs Depth

2D Cross Plot

Index Range: From 178.50 to 6803.00 ft

DEPTH-CZMD (CZMD : Data Not Found)
DEPTH-AIBH
DEPTH-AIBL (AIBL : Data Not Found)
DEPTH-AIBM



Company:	Southern California Gas Company
Well:	PORTER 72A
Field:	Aliso Canyon
County:	Los Angeles
State:	California

Schlumberger

Ultrasonic Imager

Gamma Ray - CCL

9-5/8" 47# casing